HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 35SR1250037

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: **BETHEL RD**CROSSING: **BRANCH**

LATITUDE:: N 35.34369 DEGREES LONGITUDE: W 88.82033 DEGREES

COUNTY: HARDEMAN
ROUTE: SR125
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 29.69
YEAR BUILT: 1991

201	10.1052. 11 00.02000 DEGREES	, 12/11/201211. 1001
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	CONCRETE - CHANNEL BEAM	APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	TIMBER CAP ON TIMBER PILE FOU	INDATION
BENTS:	TIMBER PILE BENT ON PILE FOUN	DATION
PIERS:	NOT APPLICABLE	
		SCOUR EVALUATION
Duides has	under a Diele of a co	
		our cannot be determined. The bridge shall be monitored for distress e in lieu of installing scour countermeasures.
		INSPECTION PROCEDURES
What Initiated the Call-out Inspection?		[] BridgeWatch Alert
		[] TDOT District or Local Maintenance Personnel
		[] THP or Local Law Enforcement Personnel
		[] Other:
Things to c	heck on a bridge during floods	<u>s:</u>
[] - Span	n movement - horizontally as w	ell as vertically
	_	n along curb line, both bridge rails and outer edge of bridge deck.
	Check for plumb of piers or be	
	ck for embankment erosion	
	k for drift build-up on piers or	bents
	· · · ·	nd compare to previous inspection
		report versus current field conditions
[]	on the latest bridge mepeenen.	
If Closure is	<u>s recommended:</u>	
Cour temp	nty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may
• • •		Supervisor (if bridge is State maintained)
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	• • •
] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.	

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[] - The bridge inspection team will work with State District maintenance or local highway maintenance



officials in establishing a detour route. Any brid	lge on the selected detour route shall be checked	
The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:	
REGION BRIDGE ENGINEER	(731) 234-9561	
DISTRICT MAINTENANCE SUPERVISOR	(731) 694-6673	
TENNESSEE HIGHWAY PATROL	(901) 543-6256	
The report shall include the date and time of the as appropriate, photographs of the bridge and s scouring has occurred, the report shall also be comments:	tream channel measurements. If significant copied to Bridge Inspection Headquarters.	
Suggested List of Equipment to conduct the Inspection	on:	
Latest Bridge Inspection Report		
Scour POA Report with the above Checklist		
Bridge Design Plans, if available		
Tape measure with weight		
Plumb bob		
Range Pole		
A 1000 Foot Roll of yellow Polyethylene Barricade Tap		
SAFETY HAZARD KEEP A	AWAY	

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24