HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 360A2430003
BRIDGE OWNER: HARDIN COUNTY
ROAD NAME: NUMBER TWO RD
CROSSING: PETTY BRANCH

LATITUDE:: N 35.11136 DEGREES LONGITUDE: W 88.02644 DEGREES

COUNTY: HARDIN
ROUTE: 0A243
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 1.82
YEAR BUILT: 1992

		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM O		
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	INT ON SOIL FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION	
		our cannot be determined. The bridge shall be monitored for distress e in lieu of installing scour countermeasures.	
		- INSPECTION PROCEDURES -	
What Initiat	ted the Call-out Inspection?	[] BridgeWatch Alert	
What initiated the Oan-Out inspection:		[] TDOT District or Local Maintenance Personnel	
		[] THP or Local Law Enforcement Personnel	
		[] Other:	
		[] Outer.	
Things to c	heck on a bridge during floods	s:	
_	movement - horizontally as w		
		n along curb line, both bridge rails and outer edge of bridge deck.	
	Check for plumb of piers or be		
	k for embankment erosion	1110.	
	k for drift build-up on piers or	hents	
		nd compare to previous inspection	
		report versus current field conditions	
[] - Veale	ew the latest bridge inspection	report versus current neid conditions	
If Closure is	recommended:		
Cour temp	nty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may	
		Supervisor (if bridge is State maintained)	
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)	
	(3) Tennessee Highway Pa	atrol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer Engineer	
] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	with State District maintenance or local highway maintenance e. Any bridge on the selected detour route shall be checked	
] - The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:	
COUNTY MAYOR'S OFFICE	(731) 925-9078	
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 925-4993	
COUNTY SHERIFF'S OFFICE	(731) 925-3377	
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.		
COMMENTS:		
Suggested List of Equipment to conduct the Latest Bridge Inspection Report	e Inspection:	
Scour POA Report with the above Checklis	t	
Bridge Design Plans, if available		
Tape measure with weight		
Plumb bob		
Range Pole		
A 1000 Foot Roll of yellow Polyethylene Ba	rricade Tape printed with the following message:	
SAFFTY HAZA	RD KEEP AWAY	

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24