HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 360A3070001 BRIDGE OWNER: HARDIN COUNTY ROAD NAME: GILLIS RD

CROSSING: HORSE CREEK

LATITUDE:: N 35.13611 DEGREES

COUNTY: HARDIN ROUTE: 0A307 SPECIAL CASE: 0 COUNTY SEQUENCE: 1 LOG MILE: 0.02

LON	NGITUDE: W 88.01458 DEGREES	5	YEAR BUILT: 1965
MAIN SPAN:	CONCRETE - TEE BEAM	- TYPE OF SUPERSTRUCTURE - APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE =	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON U		
BENTS:	CONCRETE COLUMN TWO POST B		
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION	
•	unknown foundations. Risk of sco icant flood events. Monitor bridge		bridge shall be monitored for distress termeasures.
		- INSPECTION PROCEDURES -	
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert	
	·	[] TDOT District or Loca	al Maintenance Personnel
		[] THP or Local Law En	forcement Personnel
		[] Other:	
Things to o	hook on a bridge during flood	·-	
_	heck on a bridge during floods		
	movement - horizontally as w	•	e rails and outer edge of bridge deck.
	Check for plumb of piers or be		e rails and outer edge of bridge deck.
	k for embankment erosion	1113.	
	k for drift build-up on piers or	hants	
	k pier exposure, if possible, ar		ection
	ew the latest bridge inspection		
[] - IVeAIG	w the latest bridge mapection	report versus current neia c	onditions
<u>lf Closure is</u>	recommended:		
Coun temp	nty or City Maintenance Persor	nnel. Use Barricade Tape, trat rists to stay off of the bridge	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	Supervisor (if bridge is State	maintained)
	(2) City or County Highwa	y Maintenance Official (if br	ridge is not State maintained)
	(3) Tennessee Highway P	atrol and/or local law enforce	ement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	ate District maintenance or local highway maintenance oridge on the selected detour route shall be checked	
 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:	
COUNTY MAYOR'S OFFICE	(731) 925-9078	
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 925-4993	
COUNTY SHERIFF'S OFFICE	(731) 925-3377	
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.		
COMMENTS:		
Suggested List of Equipment to conduct the Inspectatest Bridge Inspection Report	ction:	
Scour POA Report with the above Checklist		
Bridge Design Plans, if available		
Tape measure with weight		
Plumb bob		
Range Pole		
A 1000 Foot Roll of yellow Polyethylene Barricade		
SAFETY HAZARD KEE	P AWAY	

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)