HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 360A4840001
BRIDGE OWNER: HARDIN COUNTY
ROAD NAME: FRANKS LN
CROSSING: GERMANY BRANCH

LATITUDE:: N 35.14489 DEGREES
LONGITUDE: W 88.00969 DEGREES

COUNTY: HARDIN
ROUTE: 0A187
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.05
YEAR BUILT: 1075

LON	NGHUDE: W 88.00969 DEGREES		YEAR BUILT: 1975
		TYPE OF SUPERSTRUCTURE -	
MAIN SPAN:	CONCRETE - CHANNEL BEAM	APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON I	ROCK FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION —	
	unknown foundations. Risk of scr icant flood events. Monitor bridg		oridge shall be monitored for distress termeasures.
		INSPECTION PROCEDURES -	
What Initiated the Call-out Inspection		[] BridgeWatch Alert	
	-	[] TDOT District or Loca	l Maintenance Personnel
		[] THP or Local Law Enfo	orcement Personnel
		[] Other:	
[] - Span 1. 0 2. 0 [] - Chec [] - Chec	heck on a bridge during floods movement - horizontally as we Check displacement / deflectio Check for plumb of piers or be k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, and ew the latest bridge inspection	ell as vertically n along curb line, both bridge nts. bents nd compare to previous inspe	
[] - Stay Cour temp	nty or City Maintenance Persor	nnel. Use Barricade Tape, trafi rists to stay off of the bridge ι	ured and properly closed by District, fic cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	Supervisor (if bridge is State	maintained)
	() ,	y Maintenance Official (if bri	,
	• •	atrol and/or local law enforce	ment Officers as appropriate
	(4) TDOT Regional Bridge	-	
	Bridge should remain closed u TDOT bridge inspection team.		laylight visual inspection is made

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	te District maintenance or local highway maintenance idge on the selected detour route shall be checked		
[] - The bridge can be re-opened only after a TDO units and they are determined to be structural	 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(731) 925-9078		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 925-4993		
COUNTY SHERIFF'S OFFICE	(731) 925-3377		
The report shall include the date and time of the as appropriate, photographs of the bridge and	- Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.		
COMMENTS:			
Suggested List of Equipment to conduct the Inspect Latest Bridge Inspection Report Scour POA Report with the above Checklist	ion:		
Bridge Design Plans, if available			
Tape measure with weight Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	ane printed with the following message:		
SAFETY HAZADO KEED			

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24