HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 36SR1280005
BRIDGE OWNER: HARDIN COUNTY
ROAD NAME: CLIFTON RD
CROSSING: OVERFLOW

LATITUDE:: N 35.25244 DEGREES LONGITUDE: W 88.20681 DEGREES

COUNTY: HARDIN
ROUTE: 02333
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 2.49
YEAR BUILT: 1951

LON	NGITODE. W 66.20001 DEGREES	TEAN BOILT. 1931
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	CONCRETE STUB ABUTMENT ON	CONCRETE PILE FOUNDATION
BENTS:	CONCRETE PILE BENT ON PILE FO	DUNDATION
PIERS:	NOT APPLICABLE	
		SCOUR EVALUATION
•		etermined to be unstable for calculated scour conditions. No scour
countermeas	sures are installed but they are r	needed.
		INSPECTION PROCEDURES ————————————————————————————————————
What Initiated the Call-out Inspection?		[] BridgeWatch Alert
		[] TDOT District or Local Maintenance Personnel
		[] THP or Local Law Enforcement Personnel
		[] Other:
Things to c	heck on a bridge during flood:	<u>s:</u>
[] - Span	movement - horizontally as w	rell as vertically
1. C	Sheck displacement / deflection	n along curb line, both bridge rails and outer edge of bridge deck.
2. 0	Check for plumb of piers or be	nts.
	k for embankment erosion	
	k for drift build-up on piers or	
		nd compare to previous inspection
[] - Revie	w the latest bridge inspection	report versus current field conditions
f Closuro is	recommended:	
		and an advertible side of a control and an adversariant and by District
Coun temp	nty or City Maintenance Person	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may
•	• •	Supervisor (if bridge is State maintained)
- -	• •	ay Maintenance Official (if bridge is not State maintained)
	` ' ' '	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	
	Bridge should remain closed u TDOT bridge inspection team.	ntil the water recedes and a daylight visual inspection is made

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	te District maintenance or local highway maintenance idge on the selected detour route shall be checked		
[] - The bridge can be re-opened only after a TDO units and they are determined to be structural	 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(731) 925-9078		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 925-4993		
COUNTY SHERIFF'S OFFICE	(731) 925-3377		
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 			
COMMENTS:			
Suggested List of Equipment to conduct the Inspect Latest Bridge Inspection Report Scour POA Report with the above Checklist	ion:		
Bridge Design Plans, if available			
Tape measure with weight Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	ane printed with the following message:		
SAFETY HAZADO KEED			

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24