HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 37E00100001

BRIDGE OWNER: HAWKINS COUNTY

ROAD NAME: CHOPTACK RD

CROSSING: CLOUD CREEK

LATITUDE:: N 36.38920 DEGREES
LONGITUDE: W 83.11802 DEGREES

ROUTE: 01212
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.18
YEAR BUILT: 1960

COUNTY: HAWKINS

201	torrose. II controve secretary	
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS: BENTS:	CONCRETE FULL HEIGHT ABUTME NOT APPLICABLE	NT ON UNKNOWN FOUNDATION
PIERS:	CONCRETE COLUMNS WITH SOLIC	WEB WALL (DUMB BELL) ON UNKNOWN FOUNDATION
		SCOUR EVALUATION
Bridge has I	inknown foundations. Risk of soc	our cannot be determined. The bridge shall be monitored for distress
		e in lieu of installing scour countermeasures.
		INSPECTION PROCEDURES
What Initiat	and the Call aut Inamedian?	
What Initiated the Call-out Inspection?		[] BridgeWatch Alert
		[] TDOT District or Local Maintenance Personnel
		[] THP or Local Law Enforcement Personnel
		[] Other:
Things to c	heck on a bridge during floods	•
	•	
	movement - horizontally as w	•
		n along curb line, both bridge rails and outer edge of bridge deck.
	Check for plumb of piers or be	nts.
	k for embankment erosion	
	k for drift build-up on piers or	
		nd compare to previous inspection
[] - Revie	w the latest bridge inspection	report versus current field conditions
lf Closure is	recommended:	
		and a second contilled due to a second and an according along the District
Cour temp	nty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	Supervisor (if bridge is State maintained)
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer
	Bridge should remain closed u TDOT bridge inspection team.	ntil the water recedes and a daylight visual inspection is made

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[] - The bridge inspection team will work with State District maintenance or local highway maintenance



officials in establishing a detour route. Any brid prior to signing the detour route.	ge on the selected detour route shall be checked	
] - The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:	
COUNTY MAYOR'S OFFICE	(423) 272-7359	
HWY. CHIEF ADMINISTRATOR'S OFFICE	(423) 272-7370	
COUNTY SHERIFF'S OFFICE	(423) 272-4848	
The report shall include the date and time of the as appropriate, photographs of the bridge and so scouring has occurred, the report shall also be commented.	tream channel measurements. If significant copied to Bridge Inspection Headquarters.	
Suggested List of Equipment to conduct the Inspection	<u>n:</u>	
Latest Bridge Inspection Report		
Scour POA Report with the above Checklist		
Bridge Design Plans, if available		
Tape measure with weight		
Plumb bob		
Range Pole		
A 1000 Foot Roll of yellow Polyethylene Barricade Tap		
SAFETY HAZARD KEEP A	WAY	

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape