## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 38100400029

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: 140

CROSSING: BEAR CREEK

LATITUDE:: N 35.51253 DEGREES LONGITUDE: W 89.26328 DEGREES

COUNTY: HAYWOOD

ROUTE: 10040

SPECIAL CASE: 0

COUNTY SEQUENCE: 1

LOG MILE: 11.26 YEAR BUILT: 1962

		TYPE OF SUPERSTRUCTURE		
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN: NOT APPLICABLE		
		TYPE OF SUBSTRUCTURE		
ABUTMENTS:				
BENTS:		RE POST BENT ON PILE FOUNDATION		
PIERS:	NOT APPLICABLE			
		SCOUR EVALUATION		
	our critical; bridge foundations def stalled and is in good condition.	termined to be unstable for calculated scour conditions. Rip-rap protection		
		INSPECTION PROCEDURES		
What Initiat	ed the Call-out Inspection?	[ ] BridgeWatch Alert		
· · · · · · · · · · · · · · · · · · ·	ou mo cum out moposition.	[ ] TDOT District or Local Maintenance Personnel		
		[ ] THP or Local Law Enforcement Personnel		
		[ ] Other:		
Things to c	heck on a bridge during floods	<u>:</u>		
[ ] - Span	movement - horizontally as we	ell as vertically		
	•	n along curb line, both bridge rails and outer edge of bridge deck.		
	Check for plumb of piers or ben			
	k for embankment erosion			
	k for drift build-up on piers or k	bents		
	• •			
<ul><li>[ ] - Check pier exposure, if possible, and compare to previous inspection</li><li>[ ] - Review the latest bridge inspection report versus current field conditions</li></ul>				
[ ] - Nevic	w the latest bridge inspection	report versus current neia contamons		
If Closure is	recommended:			
Cour temp	nty or City Maintenance Person	cross road until bridge is secured and properly closed by District, nel. Use Barricade Tape, traffic cones and/or traffic flares as ists to stay off of the bridge until such time as the bridge may		
[ ] - Conta	act: (1) District Maintenance S	upervisor ( if bridge is State maintained )		
	(2) City or County Highway	y Maintenance Official ( if bridge is not State maintained )		
	(3) Tennessee Highway Pa	atrol and/or local law enforcement Officers as appropriate		
	(4) TDOT Regional Bridge	Engineer		
	] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.			

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



officia	•	e District maintenance or local highway maintenance dige on the selected detour route shall be checked	
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTA	ACT PERSONNEL:	TELEPHONE NUMBER:	
REGIO	N BRIDGE ENGINEER	(731) 234-9561	
DISTRI	CT MAINTENANCE SUPERVISOR	(731) 694-6673	
TENNE	SSEE HIGHWAY PATROL	(901) 543-6256	
The re	eport shall include the date and time of the propriate, photographs of the bridge and s	etion to BridgeWatch scour monitoring system. e inspection, a brief summary of findings and, etream channel measurements. If significant copied to Bridge Inspection Headquarters.	
COMMENTS:			
Suggested I	List of Equipment to conduct the Inspection	on:	
Latest Bridg	ge Inspection Report		
Scour POA	Report with the above Checklist		
•	gn Plans, if available		
•	ıre with weight		
Plumb bob			
Range Pole			
A 1000 Foot	Roll of yellow Polyethylene Barricade Tap		
	SAFETY HAZARD KEEP A	AWAY	

TDOT radio directory (State Personnel only)

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape