## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 38100400030

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: 140

CROSSING: BEAR CREEK

LATITUDE:: N 35.51250 DEGREES
LONGITUDE: W 89.26350 DEGREES

COUNTY: HAYWOOD

ROUTE: 10040

SPECIAL CASE: 0

COUNTY SEQUENCE: 1

LOG MILE: 11.26

LON	NGITUDE: W 89.26350 DEGREES	3	YEAR BUILT: 1962
MAIN SPAN:	CONCRETE - TEE BEAM	• TYPE OF SUPERSTRUCTURE • APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE =	
ARITMENTS:	CONCRETE STUB ABUTMENT ON C		
BENTS:	CONCRETE COLUMN FOUR OR MO		ION
PIERS:	NOT APPLICABLE	NE POST BENT ON FILE POUNDAT	ION
		SCOUR EVALUATION	
	our critical; bridge foundations de stalled and is in good condition.	etermined to be unstable for cal	culated scour conditions. Rip-rap protection
		INSPECTION PROCEDURES	
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert	
			al Maintenance Personnel
		[ ] THP or Local Law En	
Things to c	heck on a bridge during floods	<u>s:</u>	
1. 0	-	n along curb line, both bridge	e rails and outer edge of bridge deck.
	Check for plumb of piers or be	nts.	
	k for embankment erosion	hanta	
	k for drift build-up on piers or		action
	k pier exposure, if possible, ar	•	
[ ] - Revie	ew the latest bridge inspection	report versus current field c	onations
If Closure is	recommended:		
Coun temp	nty or City Maintenance Persor	nnel. Use Barricade Tape, trat rists to stay off of the bridge	cured and properly closed by District, ific cones and/or traffic flares as until such time as the bridge may
[ ] - Conta	act: (1) District Maintenance S	Supervisor ( if bridge is State	maintained )
	(2) City or County Highwa	y Maintenance Official ( if br	ridge is not State maintained )
	(3) Tennessee Highway P	atrol and/or local law enforce	ement Officers as appropriate
	(4) TDOT Regional Bridge		
	Bridge should remain closed until the water recedes and a daylight visual inspection is made a TDOT bridge inspection team.		

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



<ul> <li>The bridge inspection team will work with State officials in establishing a detour route. Any brid prior to signing the detour route.</li> </ul>	e District maintenance or local highway maintenance dge on the selected detour route shall be checked		
<ul> <li>The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.</li> </ul>			
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(731) 234-9561		
DISTRICT MAINTENANCE SUPERVISOR	(731) 694-6673		
TENNESSEE HIGHWAY PATROL	(901) 543-6256		
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct the Inspection  Latest Bridge Inspection Report	on:		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	pe printed with the following message:		
SAFETY HAZARD KEEP	AWAY		

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

17-Apr-19