HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 390A0430003 COUNTY: HENDERSON

BRIDGE OWNER: HENDERSON COUNTY

ROAD NAME: **UTLEY RD**CROSSING: **OVERFLOW**

LATITUDE:: N 35.77086 DEGREES
LONGITUDE: W 88.59575 DEGREES

ROUTE: 0A043

SPECIAL CASE: 0

COUNTY SEQUENCE: 1

LOG MILE: 0.88

LON	IGITUDE: W 88.59575 DEGREE	S	YEAR BUILT: 1982
		TYPE OF SUPERSTRUCT	TURE
MAIN SPAN:	PRESTRESSED CONCRETE - BOX GIRDERS - SINGLE OR SPREAD	BEAM OR APPR	. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTU	IRE -
ABUTMENTS:	CONCRETE STUB ABUTMENT ON	CONCRETE PILE FOUNDAT	ION
BENTS:	CONCRETE PILE BENT ON PILE FO	DUNDATION	
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION	
	our critical; bridge foundations d stalled and is in fair condition. So		e for calculated scour conditions. Rip-rap protection protection system are needed.
		INSPECTION PROCEDU	RES -
What Initiated the Call-out Inspection		[] BridgeWatch A	Alert
		[] TDOT District	or Local Maintenance Personnel
		[] THP or Local L	aw Enforcement Personnel
		[] Other:	
[] - Span 1. C 2. C [] - Chec [] - Chec	heck on a bridge during flood movement - horizontally as we check displacement / deflection check for plumb of piers or be k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, a ew the latest bridge inspection	vell as vertically on along curb line, both onts. bents nd compare to previou	
f Closure is	recommended:		
Coun temp	ity or City Maintenance Perso	nnel. Use Barricade Ta rists to stay off of the l	e is secured and properly closed by District, pe, traffic cones and/or traffic flares as bridge until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	Supervisor (if bridge i	s State maintained)
	(2) City or County Highwa	ay Maintenance Officia	I(if bridge is not State maintained)
	(3) Tennessee Highway P	atrol and/or local law	enforcement Officers as appropriate
	(4) TDOT Regional Bridge	e Engineer	
	Bridge should remain closed until the water recedes and a daylight visual inspection is made		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	State District maintenance or local highway maintenance y bridge on the selected detour route shall be checked		
	- The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(731) 968-0122		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 968-9201		
COUNTY SHERIFF'S OFFICE	(731) 968-7777		
The report shall include the date and time of as appropriate, photographs of the bridge	Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.		
COMMENTS:			
Suggested List of Equipment to conduct the Insp Latest Bridge Inspection Report	pection:		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricad			
SAFFTY HAZARD KI	EEP AWAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24

BRIDGE ID 390A0430003