HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 390A3540001

BRIDGE OWNER: HENDERSON COUNTY

ROAD NAME: DOYLE RD

CROSSING: BIG HURRICANE DRAINAGE

COUNTY: HENDERSON ROUTE: 0A354 SPECIAL CASE: 0 COUNTY SEQUENCE: 1

	TITUDE:: N 35.46844 DEGREE GITUDE: W 88.33731 DEGREE		LOG MILE: 1.10 YEAR BUILT: 1965
		- TYPE OF SUPERSTRUCTURE -	
MAIN SPAN:	WOOD OR TIMBER - STRINGER/MI GIRDER	ULTI-BEAM OR APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE	
	TIMBER CAP ON TIMBER PILE FO		
BENTS:	TIMBER PILE BENT ON PILE FOUN	IDATION	
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION -	
is required to		es. Rip-rap protection has been	red at bridge foundations. Immediate action installed but is in poor condition. Significant
		- INSPECTION PROCEDURES -	
What Initiated the Call-out Inspection?		[] BridgeWatch Alert	
		[] TDOT District or Loca	al Maintenance Personnel
		[] THP or Local Law Enf	
		[] Other:	
-			
Things to cl	heck on a bridge during flood	<u>s:</u>	
	movement - horizontally as w	· •	
			e rails and outer edge of bridge deck.
	Check for plumb of piers or be	ents.	
	k for embankment erosion	Lanta	
	k for drift build-up on piers or		
		nd compare to previous inspe	
[] - Kevie	w the latest bridge inspection	n report versus current field c	onditions
f Closure is	recommended:		
		across road until bridge is sec	cured and properly closed by District,
Coun temp	ty or City Maintenance Perso	nnel. Use Barricade Tape, trat rists to stay off of the bridge	fic cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance	Supervisor (if bridge is State	maintained)
	(2) City or County Highwa	ay Maintenance Official (if br	idge is not State maintained)
	(3) Tennessee Highway F	atrol and/or local law enforce	ment Officers as appropriate
	(4) TDOT Regional Bridge		
	dge should remain closed until the water recedes and a daylight visual inspection is made OT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with State officials in establishing a detour route. Any bridge prior to signing the detour route. 	District maintenance or local highway maintenance ge on the selected detour route shall be checked		
[] - The bridge can be re-opened only after a TDOT be units and they are determined to be structurally	ge can be re-opened only after a TDOT bridge inspection team checks the substructure d they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(731) 968-0122		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 968-9201		
COUNTY SHERIFF'S OFFICE	(731) 968-7777		
The report shall include the date and time of the as appropriate, photographs of the bridge and st scouring has occurred, the report shall also be c	ream channel measurements. If significant		
COMMENTS:			
Suggested List of Equipment to conduct the Inspectio	<u>n:</u>		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tap			
SAFETY HAZARD KEEP A	WAY		
A Barricade Tape Dispenser with serrated cutter			
A roll of Duct Tape			

Traffic Cones - Minimum of four (4)

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone