HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 390A4880001

BRIDGE OWNER: HENDERSON COUNTY

ROAD NAME: WILSON RD CROSSING: BRANCH

COUNTY: HENDERSON ROUTE: 0A488 SPECIAL CASE: 0 COUNTY SEQUENCE: 1

	TITUDE:: N 35.65161 DEGREES IGITUDE: W 88.52697 DEGREES			
		TYPE OF SUPERSTRUCTURE		
MAIN SPAN:	WOOD OR TIMBER - STRINGER/MU GIRDER			
		TYPE OF SUBSTRUCTURE		
	BUTMENTS: TIMBER CAP ON TIMBER PILE FOUNDATION			
BENTS:	TIMBER PILE BENT ON PILE FOUN			
PIERS:	NOT APPLICABLE			
		SCOUR EVALUATION ————————————————————————————————————		
	our critical; bridge foundations de stalled and is in good condition.	etermined to be unstable for calculated scour conditions. Rip-rap protection		
		INSPECTION PROCEDURES		
What Initiated the Call-out Inspection?		[] BridgeWatch Alert		
		[] TDOT District or Local Maintenance Personnel		
		[] THP or Local Law Enforcement Personnel		
		[] Other:		
Things to c	heck on a bridge during flood	<u>s:</u>		
[] - Span	movement - horizontally as w	ell as vertically		
1. 0	Check displacement / deflection	n along curb line, both bridge rails and outer edge of bridge deck.		
	Check for plumb of piers or be	nts.		
[] - Chec	k for embankment erosion			
	k for drift build-up on piers or			
		nd compare to previous inspection		
[] - Revie	w the latest bridge inspection	report versus current field conditions		
If Closure is	recommended:			
Coun temp	ty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may		
[] - Conta	act: (1) District Maintenance \$	Supervisor (if bridge is State maintained)		
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)		
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate		
	(4) TDOT Regional Bridge	Engineer Engineer		
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.			

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



offici	•	District maintenance or local highway maintenance lge on the selected detour route shall be checked	
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONT	ACT PERSONNEL:	TELEPHONE NUMBER:	
COUN	TY MAYOR'S OFFICE	(731) 968-0122	
HWY.	CHIEF ADMINISTRATOR'S OFFICE	(731) 968-9201	
COUN	TY SHERIFF'S OFFICE	(731) 968-7777	
The re	- Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.		
COMMENTS:			
Suggested	List of Equipment to conduct the Inspection	on:	
Latest Bridg	ge Inspection Report		
	Report with the above Checklist		
•	ign Plans, if available		
•	ure with weight		
Plumb bob			
Range Pole			
A 1000 Foot	t Roll of yellow Polyethylene Barricade Tap		
	SAFETY HAZARD KEEP A	AVVAY	

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

17-Apr-19