HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



COUNTY: HENRY ROUTE: 00902

BRIDGE ID NUMBER: 40\$80930005 BRIDGE OWNER: HENRY COUNTY ROAD NAME: **ELKHORN RD** SPECIAL CASE: 0 CROSSING: WEST SANDY CREEK COUNTY SEQUENCE: 1 LATITUDE" N 36 30200 DEGREES

	TITUDE:: N 36.30200 DEGREES	
LON	IGITUDE: W 88.16058 DEGREES	YEAR BUILT: 1942
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	STEEL CONTINUOUS - STRINGER/I	MULTI-BEAM OR APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	CONCRETE STUB ABUTMENT ON (CONCRETE PILE FOUNDATION
BENTS:	NOT APPLICABLE	
PIERS:	CONCRETE SOLID SHAFT PIER ON	TIMBER PILE FOUNDATION
		SCOUR EVALUATION
		etermined to be unstable for calculated scour conditions. Rip-rap protection ome minor repairs to the protection system are needed.
		INSPECTION PROCEDURES
What Initiated the Call-out Inspection?		[] BridgeWatch Alert
		[] TDOT District or Local Maintenance Personnel
		[] THP or Local Law Enforcement Personnel
		[] Other:
Things to cl	heck on a bridge during flood	<u>s:</u>
[] - Span	movement - horizontally as w	ell as vertically
	-	n along curb line, both bridge rails and outer edge of bridge deck.
	Check for plumb of piers or be	
	k for embankment erosion	
[] - Checl	k for drift build-up on piers or	bents
[] - Checl	k pier exposure, if possible, a	nd compare to previous inspection
[] - Revie	w the latest bridge inspection	report versus current field conditions
<u>lf Closure is</u>	recommended:	
Coun temp	ty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	Supervisor (if bridge is State maintained)
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer
	- The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.	

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with State officials in establishing a detour route. Any brid prior to signing the detour route. 	District maintenance or local highway maintenance lge on the selected detour route shall be checked		
	 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(731) 642-5212		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 642-3162		
COUNTY SHERIFF'S OFFICE	(731) 642-1672		
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct the Inspection Latest Bridge Inspection Report Scour POA Report with the above Checklist	on:		
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tap	pe printed with the following message:		
CAFETY HAZADD MEED A	MAV		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24