HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 40SR0692001

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: SR69 ALT S
CROSSING: BIG SANDY RIVER

LATITUDE:: N 36.23242 DEGREES
LONGITUDE: W 88.10411 DEGREES

COUNTY: HENRY
ROUTE: SR069
SPECIAL CASE: 2
COUNTY SEQUENCE: 1
LOG MILE: 0.12

LON	GITUDE: W 88.10411 DEGREES	YEAR BUILT: 1942	
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	PRESTRESSED CONCRETE - STRI	IGER/MULTI-BEAM APPR. SPAN: NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	NT ON CONCRETE PILE FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	CONCRETE COLUMNS WITH SOLII	WEB WALL (DUMB BELL) ON TIMBER PILE FOUNDATION	
		SCOUR EVALUATION	
		etermined to be unstable for calculated scour conditions. Rip-rap protection gnificant repairs to the protection system are needed.	'n
		INSPECTION PROCEDURES	
What Initiated the Call-out Inspection		[] BridgeWatch Alert	
		[] TDOT District or Local Maintenance Personnel	
		[] THP or Local Law Enforcement Personnel	
		[] Other:	
[] - Span 1. C 2. C [] - Checl [] - Checl	Check for plumb of piers or be k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, a	ell as vertically n along curb line, both bridge rails and outer edge of bridge deck. nts.	
f Closure is	recommended:		
Coun temp	ty or City Maintenance Person	cross road until bridge is secured and properly closed by District, anel. Use Barricade Tape, traffic cones and/or traffic flares as ists to stay off of the bridge until such time as the bridge may	
[] - Conta	act: (1) District Maintenance S	upervisor (if bridge is State maintained)	
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)	
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer	
	Bridge should remain closed u FDOT bridge inspection team.	ntil the water recedes and a daylight visual inspection is made	

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	th State District maintenance or local highway maintenance Any bridge on the selected detour route shall be checked		
- The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.			
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(731) 234-9561		
DISTRICT MAINTENANCE SUPERVISOR	(731) 571-8883		
TENNESSEE HIGHWAY PATROL	(731) 423-6635		
The report shall include the date and time as appropriate, photographs of the bridg	 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 		
COMMENTS:			
Suggested List of Equipment to conduct the In Latest Bridge Inspection Report	spection:		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barrica			
SAFFTY HAZARD	KEEP AWAY		

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

PUBLICATION DATE
07-Nov-24

A roll of Duct Tape