HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 410A2510001
BRIDGE OWNER: HICKMAN COUNTY
ROAD NAME: SUNRISE RD
CROSSING: BIG SWAN CREEK

LATITUDE:: N 35.68225 DEGREES
LONGITUDE: W 87.42975 DEGREES

COUNTY: HICKMAN
ROUTE: 0A277
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.58
YEAR BUILT: 1972

		TYPE OF SUPERSTRUCTURE		
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN: NOT APPLICABLE		
		TYPE OF SUBSTRUCTURE		
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTMEN			
BENTS:	NOT APPLICABLE			
PIERS:	CONCRETE HAMMERHEAD PIER ON	CONCRETE SPREAD FOOTING FOUNDATION		
		SCOUR EVALUATION		
Bridge has u	inknown foundations. Disk of sooi	ur cannot be determined. The bridge shall be monitored for distress		
		in lieu of installing scour countermeasures.		
		INSPECTION PROCEDURES		
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert		
	•	[] TDOT District or Local Maintenance Personnel		
		[] THP or Local Law Enforcement Personnel		
		[] Other:		
Things to c	<u>heck on a bridge during floods</u>			
[] - Span	movement - horizontally as we	II as vertically		
1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck.				
2. 0	check for plumb of piers or ben	ts.		
[] - Check for embankment erosion				
[] - Check for drift build-up on piers or bents				
[] - Check pier exposure, if possible, and compare to previous inspection				
[] - Review the latest bridge inspection report versus current field conditions				
If Closure is	recommended:			
 Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded. 				
[] - Conta	act: (1) District Maintenance Su	pervisor (if bridge is State maintained)		
	(2) City or County Highway	Maintenance Official (if bridge is not State maintained)		
	(3) Tennessee Highway Pa	trol and/or local law enforcement Officers as appropriate		
	(4) TDOT Regional Bridge	Engineer		
	 The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team. 			

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[] - The bridge inspection team will work with State District maintenance or local highway maintenance



	officials in establishing a detour route. Any brorior to signing the detour route.	idge on the selected detour route shall be checked	
	 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructurally stable. 		
<u>c</u>	CONTACT PERSONNEL:	TELEPHONE NUMBER:	
C	COUNTY MAYOR'S OFFICE	(931) 729-2492	
Н	WY. CHIEF ADMINISTRATOR'S OFFICE	(931) 729-2482	
C	COUNTY SHERIFF'S OFFICE	(931) 729-6143	
a: Se			
Sugges	sted List of Equipment to conduct the Inspect	ion:	
Latest I	Bridge Inspection Report		
Scour F	POA Report with the above Checklist		
Bridge	Design Plans, if available		
•	easure with weight		
Plumb			
Range			
A 1000	Foot Roll of yellow Polyethylene Barricade Ta		
	SAFETY HAZARD KEEP	AWAY	

TDOT radio directory (State Personnel only)

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape