HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 410A5720001

BRIDGE OWNER: HICKMAN COUNTY

ROAD NAME: FALLS HOLLOW RD

CROSSING: UPPER SINKING CREEK

LATITUDE:: N 35.66792 DEGREES

COUNTY: HICKMAN
ROUTE: 0A572
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.11
YEAR BUILT: 1995

LON	NGITUDE: W 87.65158 DEGREES		YEAR BUILT: 1995
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM OR	TYPE OF SUPERSTRUCTURE GIRDER APPR. SPAN	: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTMEN	IT ON SOIL FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION	
•	unknown foundations. Risk of sco icant flood events. Monitor bridge		e bridge shall be monitored for distress untermeasures.
		INSPECTION PROCEDURES	
What Initiated the Call-out Inspection?		[] BridgeWatch Alert	
	-	[] TDOT District or Lo	cal Maintenance Personnel
		[] THP or Local Law E	nforcement Personnel
		[] Other:	
Things to c	heck on a bridge during floods	:	
1. C 2. C	Check for plumb of piers or ben	along curb line, both brid	ge rails and outer edge of bridge deck.
	k for embankment erosion		
	k for drift build-up on piers or b		
	k pier exposure, if possible, and	•	
[] - Revie	ew the latest bridge inspection	report versus current field	conditions
lf Closure is	recommended:		
Coun temp	nty or City Maintenance Personi	nel. Use Barricade Tape, tr	ecured and properly closed by District, affic cones and/or traffic flares as e until such time as the bridge may
[] - Conta	act: (1) District Maintenance Su	upervisor (if bridge is Stat	te maintained)
	(2) City or County Highway	Maintenance Official (if	bridge is not State maintained)
	(3) Tennessee Highway Pa	trol and/or local law enford	cement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
	Bridge should remain closed un TDOT bridge inspection team.	til the water recedes and a	a daylight visual inspection is made

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[] - The bridge inspection team will work with State District maintenance or local highway maintenance



officials in establishing a	detour route. Any bridge on the selected detour route shall be checked ur route.			
[] - The bridge can be re-ope	oridge can be re-opened only after a TDOT bridge inspection team checks the substructure and they are determined to be structurally stable.			
CONTACT PERSONNEL:	TELEPHONE NUMBER:			
COUNTY MAYOR'S OFFICE	(931) 729-2492			
HWY. CHIEF ADMINISTRATOR	S OFFICE (931) 729-2482			
COUNTY SHERIFF'S OFFICE	(931) 729-6143			
The report shall include the as appropriate, photograph scouring has occurred, the	ndings from the inspection to BridgeWatch scour monitoring system. he date and time of the inspection, a brief summary of findings and, ohs of the bridge and stream channel measurements. If significant he report shall also be copied to Bridge Inspection Headquarters.			
Suggested List of Equipment to	conduct the Inspection:			
Latest Bridge Inspection Repor				
Scour POA Report with the abo				
Bridge Design Plans, if availabl	е			
Tape measure with weight				
Plumb bob				
Range Pole				
A 1000 Foot Roll of yellow Poly	ethylene Barricade Tape printed with the following message:			

SAFETY HAZARD KEEP AWAY

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Cones - Minimum of four (4)

PUBLICATION DATE
07-Nov-24

A roll of Duct Tape