HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 410A6180001

BRIDGE OWNER: HICKMAN COUNTY

ROAD NAME: HARLOWE LN

CROSSING: COPPERAS BRANCH

LATITUDE:: N 35.67937 DEGREES

LONGITUDE: W 87.44465 DEGREES

COUNTY: HICKMAN
ROUTE: 0A618
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.12
YEAR BUILT: 1994

LON	NGH ODE. W 87.44403 DEGREES	•	TEAR BOILT. 1994
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM O	R GIRDER APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	NO ABUTMENTS EXISTS (SOIL OR	ROCK SUPPORT ENDS) ON UNKNO	OWN FOUNDATION
BENTS:	NOT APPLICABLE	·	
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION -	
Dridge bee	unknown form dations. Disk of one	SCOUR EVALUATION =	builded about he manifered for distance
	icant flood events. Monitor bridge		bridge shall be monitored for distress itermeasures.
		INSPECTION PROCEDURES -	
What Initiated the Call-out Inspection?		[] BridgeWatch Alert	
		•	al Maintenance Personnel
		[] THP or Local Law En	
		[] Other:	
Things to c	heck on a bridge during floods	<u>s:</u>	
[] - Span	movement - horizontally as w	ell as vertically	
1. 0	Check displacement / deflectio	n along curb line, both bridg	e rails and outer edge of bridge deck.
2. 0	Check for plumb of piers or be	nts.	
[] - Chec	k for embankment erosion		
[] - Chec	k for drift build-up on piers or	bents	
[] - Chec	k pier exposure, if possible, ar	nd compare to previous inspe	ection
[] - Revie	ew the latest bridge inspection	report versus current field c	onditions
f Clasura is	rocommonded		
	recommended:		
Coun temp	ity or City Maintenance Persor	nnel. Use Barricade Tape, tra	cured and properly closed by District, flic cones and/or traffic flares as until such time as the bridge may
-	act: (1) District Maintenance S	unervisor (if hridge is State	maintained \
L] - Conta	• •	•	ridge is not State maintained)
	` , , ,	•	ement Officers as appropriate
	(4) TDOT Regional Bridge		mont officers as appropriate
[] - The F	()	•	daylight visual inspection is made
	TDOT bridge inspection team.	inii iilo wator roocaca arla a t	adyngni vioddi mopeonom is made

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	te District maintenance or local highway maintenance ridge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 729-2492		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 729-2482		
COUNTY SHERIFF'S OFFICE	(931) 729-6143		
The report shall include the date and time of the as appropriate, photographs of the bridge and	- Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.		
COMMENTS:			
Suggested List of Equipment to conduct the Inspec	tion:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade T			
SAFETY HAZARD KEEF	PAWAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24