HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 41100400007 COUNTY: HICKMAN BRIDGE OWNER: STATE OF TENNESSEE **ROUTE: 10040** SPECIAL CASE: 0 ROAD NAME: 140 CROSSING: SUGAR CREEK COUNTY SEQUENCE: 1 LATITUDE:: N 35.88480 DEGREES LOG MILE: 2.71 LONGITUDE: W 87.66648 YEAR BUILT: 1965 **DEGREES** TYPE OF SUPERSTRUCTURE MAIN SPAN: PRESTRESSED CONCRETE CONTINUOUS -APPR. SPAN: NOT APPLICABLE STRINGER/MULTI-BEAM OR GIRDER TYPE OF SUBSTRUCTURE ABUTMENTS: CONCRETE STUB ABUTMENT ON STEEL PILE FOUNDATION BENTS: CONCRETE COLUMN THREE POST BENT ON STEEL PILE FOUNDATION PIERS: **NOT APPLICABLE SCOUR EVALUATION** Bridge is scour critical; bridge foundations determined to be unstable for calculated scour conditions. Rip-rap protection has been installed and is in good condition. **INSPECTION PROCEDURES** What Initiated the Call-out Inspection? [] BridgeWatch Alert [] TDOT District or Local Maintenance Personnel [] THP or Local Law Enforcement Personnel [] Other: Things to check on a bridge during floods: [] - Span movement - horizontally as well as vertically 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck. 2. Check for plumb of piers or bents. [] - Check for embankment erosion [] - Check for drift build-up on piers or bents [] - Check pier exposure, if possible, and compare to previous inspection [] - Review the latest bridge inspection report versus current field conditions If Closure is recommended: [] - Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.

PUBLICATION DATE

17-Apr-19

BRIDGE ID 41100400007

(2) City or County Highway Maintenance Official (if bridge is not State maintained) (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate

[] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made

[] - Contact: (1) District Maintenance Supervisor (if bridge is State maintained)

(4) TDOT Regional Bridge Engineer

by a TDOT bridge inspection team.

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	tate District maintenance or local highway maintenance bridge on the selected detour route shall be checked
[] - The bridge can be re-opened only after a TD units and they are determined to be structured.	OT bridge inspection team checks the substructure ally stable.
CONTACT PERSONNEL:	TELEPHONE NUMBER:
REGION BRIDGE ENGINEER	(615) 476-8860
DISTRICT MAINTENANCE SUPERVISOR	(931) 205-6399
TENNESSEE HIGHWAY PATROL	(931) 766-1425
as appropriate, photographs of the bridge an	the inspection, a brief summary of findings and, and stream channel measurements. If significant be copied to Bridge Inspection Headquarters.
Suggested List of Equipment to conduct the Inspe	ction:
Latest Bridge Inspection Report	
Scour POA Report with the above Checklist	
Bridge Design Plans, if available	
Tape measure with weight	
Plumb bob	
Range Pole	
A 1000 Foot Roll of yellow Polyethylene Barricade	Tape printed with the following message:
SAFETY HAZARD KEE	EP AWAY
A Barricade Tape Dispenser with serrated cutter	

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

PUBLICATION DATE
17-Apr-19