## **HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT**



BRIDGE ID NUMBER: 430A2050001

BRIDGE OWNER: HUMPHREYS COUNTY ROAD NAME: W LITTLE HURRICANE CR R CROSSING: HURRICANE CREEK

LATITUDE:: N 36.03895 DEGREES

COUNTY: HUMPHREYS ROUTE: 0A205 SPECIAL CASE: 0 COUNTY SEQUENCE: 1 LOG MILE: 2.25

LON	NGITUDE: W 87.63968 DEGREES		YEAR BUILT: 1983
		TYPE OF SUPERSTRUCTURE —	
MAIN SPAN:	PRESTRESSED CONCRETE CONTIN BEAM OR GIRDERS - SINGLE OR SE		NOT APPLICABLE
		TYPE OF SUBSTRUCTURE -	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON S	TEEL PILE FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	CONCRETE SOLID SHAFT PIER ON	STEEL PILE FOUNDATION	
		SCOUR EVALUATION —	
	our critical; bridge foundations de stalled but is in poor condition. Sig		ulated scour conditions. Rip-rap protection n system are needed.
		INSPECTION PROCEDURES —	
What Initiated the Call-out Inspection		[ ] BridgeWatch Alert	
		[ ] TDOT District or Local	Maintenance Personnel
		[ ] THP or Local Law Enfo	orcement Personnel
		[ ] Other:	
[ ] - Span 1. C 2. C [ ] - Chec [ ] - Chec	heck on a bridge during floods movement - horizontally as we check displacement / deflection check for plumb of piers or ben k for embankment erosion k for drift build-up on piers or I k pier exposure, if possible, an ew the latest bridge inspection	ell as vertically n along curb line, both bridge nts. pents d compare to previous inspec	
If Closure is	recommended:		
Coun temp	nty or City Maintenance Person	nel. Use Barricade Tape, traff	red and properly closed by District, ic cones and/or traffic flares as ntil such time as the bridge may
[ ] - Contact: (1) District Maintenance Supervisor ( if bridge is State maintained )			
	(2) City or County Highway	Maintenance Official ( if brid	dge is not State maintained )
	(3) Tennessee Highway Pa	trol and/or local law enforcen	nent Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.		

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[ ] - The bridge inspection team will work with State District maintenance or local highway maintenance



officials in establishing a detour route. Any brid	lge on the selected detour route shall be checked		
[ ] - The bridge can be re-opened only after a TDOT units and they are determined to be structurally	ge can be re-opened only after a TDOT bridge inspection team checks the substructure		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 296-7795		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 296-2121		
COUNTY SHERIFF'S OFFICE	(931) 296-2301		
The report shall include the date and time of the as appropriate, photographs of the bridge and s scouring has occurred, the report shall also be COMMENTS:	tream channel measurements. If significant copied to Bridge Inspection Headquarters.		
Suggested List of Equipment to conduct the Inspection	on:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tap			
SAFETY HAZARD KEEP A	AWAY		

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24