HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 430A2540003

BRIDGE OWNER: HUMPHREYS COUNTY

ROAD NAME: **E BLUE CR RD** CROSSING: **BLUE CREEK**

LATITUDE:: N 36.06032 DEGREES
LONGITUDE: W 87.71647 DEGREES

COUNTY: HUMPHREYS
ROUTE: 0A254
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 4.26

LON	NGITUDE: W 87.71647 DEGREES		YEAR BUILT: 1989
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM OR	TYPE OF SUPERSTRUCTURE - GIRDER APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE =	
ABUTMENTS:	TIMBER CAP ON TIMBER PILE FOUN	IDATION	
BENTS:	TIMBER PILE BENT ON PILE FOUND	ATION	
PIERS:	NOT APPLICABLE		
		OCCUP FVALUATION	
D : 1		SCOUR EVALUATION =	
•	inknown foundations. Risk of scot icant flood events. Monitor bridge		bridge shall be monitored for distress termeasures.
		INSPECTION PROCEDURES =	
What Initiated the Call-out Inspection?		[] BridgeWatch Alert	
		[] TDOT District or Loca	al Maintenance Personnel
		[] THP or Local Law Ent	forcement Personnel
		[] Other:	
Things to cl	heck on a bridge during floods:	<u>.</u>	
1. C	<u>-</u>	along curb line, both bridge	e rails and outer edge of bridge deck.
	Check for plumb of piers or ben	IS.	
	k for embankment erosion	onto	
	k for drift build-up on piers or b		action
	k pier exposure, if possible, and		
[] - Revie	ew the latest bridge inspection i	eport versus current field c	onditions
If Closure is	recommended:		
[] - Stay a	at bridge with vehicle pulled ac		cured and properly closed by District,
temp			ffic cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance Su	pervisor (if bridge is State	maintained)
	(2) City or County Highway	Maintenance Official (if br	ridge is not State maintained)
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	•	ement Officers as appropriate
	(4) TDOT Regional Bridge I	Engineer	-
	- The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	vork with State District maintenance or local highway maintenance route. Any bridge on the selected detour route shall be checked		
	 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 296-7795		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 296-2121		
COUNTY SHERIFF'S OFFICE	(931) 296-2301		
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct Latest Bridge Inspection Report	•		
Scour POA Report with the above Chec Bridge Design Plans, if available	KIIST		
Tape measure with weight			
Plumb bob			
Range Pole			
_	Barricade Tape printed with the following message:		
-	AZARD KEEP AWAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24