HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 43SR0130025

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: N CHURCH ST CROSSING: TRACE CREEK

LATITUDE:: N 36.08573 DEGREES LONGITUDE: W 87.79337 DEGREES

COUNTY: HUMPHREYS
ROUTE: SR013
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 19.35
YEAR BUILT: 1935

		TYPE OF SUPERSTRUCTURE -	
MAIN SPAN:	CONCRETE CONTINUOUS - TEE BE		CONCRETE - TEE BEAM
		TYPE OF SUBSTRUCTURE -	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	NT ON TIMBER PILE FOUNDATION	
BENTS:	CONCRETE COLUMN TWO POST B	ENT ON TIMBER PILE FOUNDATION	ı
PIERS:	CONCRETE SOLID SHAFT PIER ON	TIMBER PILE FOUNDATION	
		SCOUR EVALUATION -	
Bridge is so	our critical: bridge foundations de		culated scour conditions. Monitor bridge in
•	ling scour countermeasures.	termined to be dristable for calc	sulated scour conditions. Monitor bridge in
		INSPECTION PROCEDURES -	
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert	
		[] TDOT District or Loca	Il Maintenance Personnel
		[] THP or Local Law Enfo	orcement Personnel
		[] Other:	
This was to a	haalaan a buidan duuinn flaada	_	
_	heck on a bridge during floods		
	movement - horizontally as we	•	
	•		e rails and outer edge of bridge deck.
	Check for plumb of piers or ber	its.	
	k for embankment erosion	honto	
	k for drift build-up on piers or l k pier exposure, if possible, an		ection
	ew the latest bridge inspection		
[] - I/GAIG	w the latest bridge inspection	report versus current neia co	Juliums
If Closure is	recommended:		
 Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded. 			
[] - Conta	act: (1) District Maintenance S	upervisor (if bridge is State	maintained)
	(2) City or County Highwa	y Maintenance Official (if bri	idge is not State maintained)
	(3) Tennessee Highway Pa	atrol and/or local law enforce	ment Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
	The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	te District maintenance or local highway maintenance ridge on the selected detour route shall be checked		
	he bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(615) 476-8860		
DISTRICT MAINTENANCE SUPERVISOR	(931) 205-6399		
TENNESSEE HIGHWAY PATROL	(615) 741-3181		
[] - Summarize and submit findings from the inspection of the report shall include the date and time of the as appropriate, photographs of the bridge and scouring has occurred, the report shall also be	he inspection, a brief summary of findings and, I stream channel measurements. If significant		
COMMENTS:			
Suggested List of Equipment to conduct the Inspec	tion:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole	and uninted with the following manager.		
A 1000 Foot Roll of yellow Polyethylene Barricade T SAFETY HAZARD KEEF			
SAFELT HAZARU KEEP	AVVAI		

TDOT radio directory (State Personnel only)

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape