Rev. 07-24-15		IWAY BRIDGE SCOUR	TDOT		
	PLA	N OF ACTION REPORT	TN Department of Transportation		
BRIDGE ID N	IUMBER: 470B2120001		COUNTY: KNOX		
BRIDGE	OWNER: CITY OF KNOXVILLE		ROUTE: 0B212		
ROA	D NAME: GREENWAY RD		SPECIAL CASE: 0		
	OSSING: FIRST CREEK		COUNTY SEQUENCE: 1		
	TITUDE:: N 36.02028 DEGREES		LOG MILE: 0.01		
LON	GITUDE: W 83.92423 DEGREES		YEAR BUILT: 1930		
		TYPE OF SUPERSTRUCTURE			
MAIN SPAN:	CONCRETE CONTINUOUS - CULVE FRAME CULVERTS)	RT (INCLUDES APPR. SPAN:	NOT APPLICABLE		
		TYPE OF SUBSTRUCTURE			
ABUTMENTS:	CONCRETE BOX TYPE ON CONCR	TE SPREAD FOOTING FOUNDATI	N		
BENTS:	NOT APPLICABLE				
PIERS:	PIER WALL FOR CONCRETE BOX ON CONCRETE SPREAD FOOTING FOUNDATION				
		SCOUR EVALUATION			
	nknown foundations. Risk of sco cant flood events. Monitor bridg		bridge shall be monitored for distress ntermeasures.		
		INSPECTION PROCEDURES			
What Initiate	ed the Call-out Inspection?	[] BridgeWatch Alert			
		[] TDOT District or Loc	al Maintenance Personnel		

[] THP or Local Law Enforcement Personnel

[] Other: _____

Things to check on a bridge during floods:

- [] Span movement horizontally as well as vertically
 - 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck.
 - 2. Check for plumb of piers or bents.
- [] Check for embankment erosion
- [] Check for drift build-up on piers or bents
- [] Check pier exposure, if possible, and compare to previous inspection
- [] Review the latest bridge inspection report versus current field conditions

If Closure is recommended:

- [] Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.
- [] Contact: (1) District Maintenance Supervisor (if bridge is State maintained)
 - (2) City or County Highway Maintenance Official (if bridge is not State maintained)
 - (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate
 - (4) TDOT Regional Bridge Engineer
- [] The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.

PUBLICATION DATE

07-Nov-24



- [] The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route.
- [] The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.

CONTACT PERSONNEL:	TELEPHONE NUMBER:
CITY MAYOR'S OFFICE	(865) 215-2040
CITY ENGINEER'S OFFICE	(865) 215-2148
POLICE OFFICE	(865) 215-7229
PUBLIC WORKS DIRECTOR	(865) 215-2060

[] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.

COMMENTS:

Suggested List of Equipment to conduct the Inspection:

Latest	Bridge	Inspection	Report
Eatoot	Dilago	mopoonon	1.0poit

Scour POA Report with the above Checklist

Bridge Design Plans, if available

Tape measure with weight

Plumb bob

Range Pole

A 1000 Foot Roll of yellow Polyethylene Barricade Tape printed with the following message:

SAFETY HAZARD KEEP AWAY

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)

PUBLICATION DATE

07-Nov-24