## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 47S24080001

BRIDGE OWNER: CITY OF KNOXVILLE

ROAD NAME: BOYD BR PK

CROSSING: Helsten B /B. Shores Dr.

COUNTY

CROSSING: Holston R./R. Shores Dr.
LATITUDE:: N 35.98478 DEGREES
LONGITUDE: W 83.85877 DEGREES

ROUTE: 01124
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 2.93
YEAR BUILT: 1949

COUNTY: KNOX

		TYPE OF SUPERSTRUCTURE =	
MAIN SPAN:	STEEL CONTINUOUS - TRUSS - THR		CONCRETE - TEE BEAM
		TYPE OF SUBSTRUCTURE =	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON ST		
BENTS:	CONCRETE COLUMN TWO POST BE	NT ON UNKNOWN FOUNDATION	
PIERS:	CONCRETE SOLID SHAFT PIER ON U	JNKNOWN FOUNDATION	
		SCOUR EVALUATION =	
Bridge has i	inknown foundations. Risk of scor		bridge shall be monitored for distress
	ficant flood events. Monitor bridge		
		INSPECTION PROCEDURES -	
What Initiat	ted the Call-out Inspection?	[ ] BridgeWatch Alert	
		[ ] TDOT District or Loca	al Maintenance Personnel
		[ ] THP or Local Law Enf	forcement Personnel
		[ ] Other:	
Things to c	heck on a bridge during floods:		
[ ] - Span	movement - horizontally as we	ll as vertically	
1. (	Check displacement / deflection	along curb line, both bridge	e rails and outer edge of bridge deck.
	Check for plumb of piers or ben	is.	
	k for embankment erosion		
	k for drift build-up on piers or b		
	k pier exposure, if possible, and		
[ ] - Revie	ew the latest bridge inspection i	eport versus current field co	onditions
<u>lf Closure is</u>	recommended:		
Cour temp	<ul> <li>Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.</li> </ul>		
-	act: (1) District Maintenance Su	pervisor ( if bridge is State	maintained )
		·	idge is not State maintained )
	(3) Tennessee Highway Pa	rol and/or local law enforce	ment Officers as appropriate
	(4) TDOT Regional Bridge I	Engineer	
	<ul> <li>The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.</li> </ul>		

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[ ] - The bridge inspection team will work with State District maintenance or local highway maintenance



officials in establishing a detour route. prior to signing the detour route.	Any bridge on the selected detour route shall be checked			
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.			
CONTACT PERSONNEL:	TELEPHONE NUMBER:			
CITY MAYOR'S OFFICE	(865) 215-2040			
CITY ENGINEER'S OFFICE	(865) 215-2148			
POLICE OFFICE	(865) 215-7229			
PUBLIC WORKS DIRECTOR	(865) 215-2060			
COMMENTS:	also be copied to Bridge Inspection Headquarters.			
Suggested List of Equipment to conduct the In	nspection:			
Latest Bridge Inspection Report Scour POA Report with the above Checklist				
Bridge Design Plans, if available				
Tape measure with weight				
Plumb bob				
Range Pole				
A 1000 Foot Roll of yellow Polyethylene Barrio	cade Tape printed with the following message:			
SAFETY HAZARD	KEEP AWAY			
A Barricade Tape Dispenser with serrated cutt	ter			

## **PUBLICATION DATE**

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone