Rev. 07-24-15		WAY BRIDGE SCOUR TDOT NOF ACTION REPORT TN TN TDOT Department of Transportation		
BRIDGE ID N	NUMBER: 47S24120003	COUNTY: KNOX		
BRIDGE	OWNER: KNOX COUNTY	ROUTE: 01289		
ROA	D NAME: WASHINGTON PIKE	SPECIAL CASE: 0		
CR	OSSING: MURPHY CREEK	COUNTY SEQUENCE: 1		
LA	TITUDE:: N 36.05510 DEGREES	LOG MILE: 2.09		
LON	IGITUDE: W 83.87037 DEGREES	YEAR BUILT: 1942		
		TYPE OF SUPERSTRUCTURE		
MAIN SPAN:	CONCRETE CONTINUOUS - CULVE FRAME CULVERTS)	RT (INCLUDES APPR. SPAN: NOT APPLICABLE		
		TYPE OF SUBSTRUCTURE		
ABUTMENTS:	CONCRETE BOX TYPE ON CONCRE	TE SPREAD FOOTING FOUNDATION		
BENTS:	NOT APPLICABLE			
PIERS:	PIER WALL FOR CONCRETE BOX ON CONCRETE SPREAD FOOTING FOUNDATION			
		SCOUR EVALUATION		
		our cannot be determined. The bridge shall be monitored for distress in lieu of installing scour countermeasures.		
What Initiated the Call-out Inspection?		[] BridgeWatch Alert		
		[] TDOT District or Local Maintenance Personnel		

- [] THP or Local Law Enforcement Personnel
- [] Other: _____

Things to check on a bridge during floods:

- [] Span movement horizontally as well as vertically
 - 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck.
 - 2. Check for plumb of piers or bents.
- [] Check for embankment erosion
- [] Check for drift build-up on piers or bents
- [] Check pier exposure, if possible, and compare to previous inspection
- [] Review the latest bridge inspection report versus current field conditions

If Closure is recommended:

- [] Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.
- [] Contact: (1) District Maintenance Supervisor (if bridge is State maintained)
 - (2) City or County Highway Maintenance Official (if bridge is not State maintained)
 - (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate
 - (4) TDOT Regional Bridge Engineer
- [] The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.

Pι	JBL	ΓΙΟΝ	DATE

07-Nov-24



- [] The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route.
- [] The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.

CONTACT PERSONNEL:	TELEPHONE NUMBER:
COUNTY MAYOR'S OFFICE	(865) 215-2005
HWY. CHIEF ADMINISTRATOR'S OFFICE	(865) 215-5800
COUNTY SHERIFF'S OFFICE	(865) 215-2432

[] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.

COMMENTS: _____

Suggested List of Equipment to conduct the Inspection:

Latest Bridge Inspection Report

Scour POA Report with the above Checklist

Bridge Design Plans, if available

Tape measure with weight

Plumb bob

Range Pole

A 1000 Foot Roll of yellow Polyethylene Barricade Tape printed with the following message:

SAFETY HAZARD KEEP AWAY

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)

PUBLICATION DATE