HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 49SR0030009

BRIDGE OWNER: STATE OF TENNESSEE ROAD NAME: **JERE B FORD HWY** CROSSING: DOUBLE BRANCH

COUNTY: LAUDERDALE ROUTE: SR003 SPECIAL CASE: 0 COUNTY SEQUENCE: 1

	TITUDE:: N 35.85189 DEGREES IGITUDE: W 89.44067 DEGREES	LOG MILE: 18.12 YEAR BUILT: 1963
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	PRESTRESSED CONCRETE - STRIN OR GIRDER	IGER/MULTI-BEAM APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	CONCRETE STUB ABUTMENT ON C	ONCRETE PILE FOUNDATION
BENTS:	CONCRETE PILE BENT ON PILE FO	UNDATION
PIERS:	NOT APPLICABLE	
		SCOUR EVALUATION
		termined to be unstable for calculated scour conditions. Rip-rap protection me minor repairs to the protection system are needed.
		INSPECTION PROCEDURES ————————————————————————————————————
What Initiated the Call-out Inspection?		[] BridgeWatch Alert
		[] TDOT District or Local Maintenance Personnel
		[] THP or Local Law Enforcement Personnel
		[] Other:
[] - Span 1. C 2. C [] - Chec [] - Chec	Check for plumb of piers or ber k for embankment erosion k for drift build-up on piers or l k pier exposure, if possible, an	ell as vertically n along curb line, both bridge rails and outer edge of bridge deck. nts.
<u>If Closure is</u>	recommended:	
Coun temp	ity or City Maintenance Person	cross road until bridge is secured and properly closed by District, nel. Use Barricade Tape, traffic cones and/or traffic flares as ists to stay off of the bridge until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	upervisor (if bridge is State maintained)
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)
	(3) Tennessee Highway Pa	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer
	e Bridge should remain closed until the water recedes and a daylight visual inspection is made a TDOT bridge inspection team.	

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	ate District maintenance or local highway maintenance oridge on the selected detour route shall be checked	
 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:	
REGION BRIDGE ENGINEER	(731) 234-9561	
DISTRICT MAINTENANCE SUPERVISOR	(901) 484-2610	
TENNESSEE HIGHWAY PATROL	(901) 543-6256	
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.		
COMMENTS:		
Suggested List of Equipment to conduct the Inspec	ction:	
Latest Bridge Inspection Report		
Scour POA Report with the above Checklist		
Bridge Design Plans, if available		
Tape measure with weight		
Plumb bob		
Range Pole		
A 1000 Foot Roll of yellow Polyethylene Barricade	Tape printed with the following message:	
SAFETY HAZARD KEE	P AWAY	

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)