## **HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT**



BRIDGE ID NUMBER: 49SR0190021

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: STATE HWY 19 CROSSING: OVERFLOW

LATITUDE" N 35 77372 DEGREES

COUNTY: LAUDERDALE ROUTE: SR019 SPECIAL CASE: 0 COUNTY SEQUENCE: 1 LOG MILE: 10.83

LON	IGITUDE: W 89.68583 DEGREE	YEAR BUILT: 1988
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	PRESTRESSED CONCRETE CONT STRINGER/MULTI-BEAM OR GIRD	
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	CONCRETE STUB ABUTMENT ON	CONCRETE PILE FOUNDATION
BENTS:	CONCRETE PILE BENT ON PILE FO	DUNDATION
PIERS:	NOT APPLICABLE	
		SCOUR EVALUATION
event. Deter	ioration of channel protection or ed and is in fair condition. Some	have been installed to reduce the risk of bridge failure during a flood riprap should be reported to TDOT for assessment. Rip-rap protection has minor repairs to the protection system are needed.
		INSPECTION PROCEDURES ————————————————————————————————————
What Initiat	ed the Call-out Inspection?	[ ] BridgeWatch Alert
		[ ] TDOT District or Local Maintenance Personnel
		[ ] THP or Local Law Enforcement Personnel [ ] Other:
		[ ] Other:
Things to c	heck on a bridge during flood	s:
_		
	movement - horizontally as w Sheck displacement / deflection	n along curb line, both bridge rails and outer edge of bridge deck.
	Check for plumb of piers or be	
	k for embankment erosion	
	k for drift build-up on piers or	bents
	• •	nd compare to previous inspection
		report versus current field conditions
	<b>.</b>	•
<u>lf Closure is</u>	recommended:	
Coun temp	ity or City Maintenance Perso	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may
[ ] - Conta	act: (1) District Maintenance	Supervisor ( if bridge is State maintained )
	(2) City or County Highwa	y Maintenance Official ( if bridge is not State maintained )
	(3) Tennessee Highway F	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer Engineer
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.	

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	te District maintenance or local highway maintenance idge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(731) 234-9561		
DISTRICT MAINTENANCE SUPERVISOR	(901) 484-2610		
TENNESSEE HIGHWAY PATROL	(901) 543-6256		
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
	<u> </u>		
Suggested List of Equipment to conduct the Inspect	ion:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	ape printed with the following message:		
SAFETY HAZARD KEEP	AWAY		
A Barricade Tape Dispenser with serrated cutter			
A roll of Duct Tape			

Traffic Cones - Minimum of four (4)

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone