HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 50009320005

BRIDGE OWNER: LAWRENCE COUNTY
ROAD NAME: FALL RIVER RD

CROSSING: EAST FORK OF SUGAR CREEK
LATITUDE:: N 35.14421 DEGREES
LONGITUDE: W 87.24776 DEGREES

COUNTY: LAWRENCE
ROUTE: 00932
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 8.93
YEAR BUILT: 1950

	TYPE OF SUPE	RSTRUCTURE	
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM OR GIRDER	APPR. SPAN: NOT APPLICABLE	
	TYPE OF SUB	STRUCTURE	
ABUTMENTS:	ABUTMENTS: CONCRETE FULL HEIGHT ABUTMENT ON ROCK FOUNDATION		
BENTS:	NOT APPLICABLE		
PIERS:	CONCRETE SOLID SHAFT PIER ON ROCK FOUNDAT	ON	
	SCOUR EV	ALUATION	
		etermined. The bridge shall be monitored for distress	
during signifi	nificant flood events. Monitor bridge in lieu of insta	ling scour countermeasures.	
	INSPECTION P	ROCEDURES	
What Initiate	ated the Call-out Inspection? [] Bridge	Watch Alert	
	[] TDOT	District or Local Maintenance Personnel	
	[] THP o	Local Law Enforcement Personnel	
	[] Other:		
Things to c	check on a bridge during floods:		
_			
	n movement - horizontally as well as vertically		
	-	ne, both bridge rails and outer edge of bridge deck.	
	Check for plumb of piers or bents.		
[] - Check for embankment erosion			
	[] - Check for drift build-up on piers or bents		
[] - Check pier exposure, if possible, and compare to previous inspection[] - Review the latest bridge inspection report versus current field conditions			
[] - Kevie	iew the latest bridge inspection report versus	current neia conditions	
If Clasura is	is recommended:		
Coun temp	ay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, ounty or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as imporary measures to warn motorists to stay off of the bridge until such time as the bridge may properly closed and barricaded.		
-] - Contact: (1) District Maintenance Supervisor (if bridge is State maintained)		
	• • • • • • • • • • • • • • • • • • • •	e Official (if bridge is not State maintained)	
		cal law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge Engineer		

PUBLICATION DATE

by a TDOT bridge inspection team.

[] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with State officials in establishing a detour route. Any bridge prior to signing the detour route. 	District maintenance or local highway maintenance ge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 762-7700		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 762-4272		
COUNTY SHERIFF'S OFFICE	(931) 762-3626		
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 			
COMMENTS:			
Suggested List of Equipment to conduct the Inspection	<u>n:</u>		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tape			
SAFETY HAZARD KEEP A	WAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24