## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 500A6450003

BRIDGE OWNER: **CITY OF LAWRENCEBURG** ROAD NAME: **OLD WAYNESBORO HWY.** 

CROSSING: SHOAL CREEK

LATITUDE:: N 35.24203 DEGREES LONGITUDE: W 87.35378 DEGREES

COUNTY: LAWRENCE
ROUTE: 0A645
SPECIAL CASE: 0
COUNTY SEQUENCE: 1

LOG MILE: 0.45

LON	IGITUDE: W 87.35378 DEGREES		YEAR BUILT: 1933	
		TYPE OF SUPERSTRUCTURE		
MAIN SPAN:	STEEL - TRUSS - THRU	APPR. SPAN: COM	NCRETE - TEE BEAM	
		TYPE OF SUBSTRUCTURE -		
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTMENT ON CONCRETE SPREAD FOOTING FOUNDATION			
BENTS:	CONCRETE COLUMN TWO POST BENT ON CONCRETE SPREAD FOOTING FOUNDATION			
PIERS:	RS: CONCRETE SOLID SHAFT PIER ON CONCRETE SPREAD FOOTING FOUNDATION			
		SCOUR EVALUATION -		
		ur cannot be determined. The bridg in lieu of installing scour counterme		
		INSPECTION PROCEDURES -		
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert		
	•	[ ] TDOT District or Local Mai	intenance Personnel	
		[ ] THP or Local Law Enforce	ment Personnel	
		[ ] Other:		
1. 0 2. 0 [ ] - Checl [ ] - Checl	Check for plumb of piers or ber k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, an	along curb line, both bridge rails	n	
If Closure is	recommended:			
Coun temp	ty or City Maintenance Person	ross road until bridge is secured nel. Use Barricade Tape, traffic co sts to stay off of the bridge until	ones and/or traffic flares as	
[ ] - Conta	act: (1) District Maintenance S	upervisor ( if bridge is State mair	ntained)	
	(2) City or County Highwa	Maintenance Official (if bridge	is not State maintained )	
	(3) Tennessee Highway Pa	trol and/or local law enforcement	t Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer		
	- The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.			

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	ite District maintenance or local highway maintenance ridge on the selected detour route shall be checked			
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.			
CONTACT PERSONNEL:	TELEPHONE NUMBER:			
CITY MAYOR'S OFFICE	(931) 762-4459			
POLICE OFFICE	(931) 762-2276			
[ ] - Summarize and submit findings from the insp The report shall include the date and time of t as appropriate, photographs of the bridge and scouring has occurred, the report shall also b	he inspection, a brief summary of findings and, I stream channel measurements. If significant			
COMMENTS:				
	·			
Suggested List of Equipment to conduct the Inspec	tion:			
Latest Bridge Inspection Report				
Scour POA Report with the above Checklist				
Bridge Design Plans, if available				
Tape measure with weight				
Plumb bob				
Range Pole				
A 1000 Foot Roll of yellow Polyethylene Barricade T				
SAFETY HAZARD KEEP	PAWAY			
A Barricade Tape Dispenser with serrated cutter				
A roll of Duct Tape				
Traffic Cones - Minimum of four (4)				
Traffic Safety Flares - Minimum of four (4) or set of	_			
TDOT two-way radio (State Personnel only) and/or of	cellular telephone			

**TDOT radio directory (State Personnel only)**