## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 51S61960009
BRIDGE OWNER: LEWIS COUNTY
ROAD NAME: SEIBER RIDGE RD
CROSSING: BUFFALO RIVER

LATITUDE:: N 35.45283 DEGREES

LONGITUDE: W 87.60358 DEGREES

COUNTY: LEWIS
ROUTE: 05563
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 4.20
YEAR BUILT: 1967

LON	IGITUDE: W 87.60358 DEGREES	YEAR BUILT: 1967
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	STEEL CONTINUOUS - STRINGER/GIRDER	MULTI-BEAM OR APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	CONCRETE STUB ABUTMENT ON	STEEL PILE FOUNDATION
BENTS:	NOT APPLICABLE	
PIERS:	CONCRETE HAMMERHEAD PIER C	N STEEL PILE FOUNDATION
		SCOUR EVALUATION
	our critical; bridge foundations de sures are installed but they are r	etermined to be unstable for calculated scour conditions. No scour eeded.
		INSPECTION PROCEDURES
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert
	·	[ ] TDOT District or Local Maintenance Personnel
		THP or Local Law Enforcement Personnel
		[ ] Other:
Things to cl	heck on a bridge during flood	<u>s:</u>
1. C 2. C [ ] - Checl [ ] - Checl	Check for plumb of piers or be k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, a	n along curb line, both bridge rails and outer edge of bridge deck. nts.
f Closure is	recommended:	
Coun temp	ty or City Maintenance Person	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may
[ ] - Conta	act: (1) District Maintenance S	Supervisor ( if bridge is State maintained )
	(2) City or County Highwa	y Maintenance Official ( if bridge is not State maintained )
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer
	Bridge should remain closed บ FDOT bridge inspection team.	ntil the water recedes and a daylight visual inspection is made

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



<ul> <li>The bridge inspection team will work with State officials in establishing a detour route. Any brid prior to signing the detour route.</li> </ul>	e District maintenance or local highway maintenance dge on the selected detour route shall be checked		
	<ul> <li>The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.</li> </ul>		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 796-3378		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 796-2287		
COUNTY SHERIFF'S OFFICE	(931) 796-5096		
<ul> <li>Summarize and submit findings from the inspection to BridgeWatch scour monitoring system.         The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.     </li> </ul>			
COMMENTS:			
Suggested List of Equipment to conduct the Inspecti	on:		
Latest Bridge Inspection Report Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	pe printed with the following message:		
SAFETY HAZARD KEEP	AWAY		

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)