HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 52019720001

BRIDGE OWNER: LINCOLN COUNTY

ROAD NAME: CHEATHAM RD

CROSSING: COLDWATER CREEK

LATITUDE:: N 35.08383 DEGREES

LONGITUDE: W 86.73462 DEGREES

COUNTY: LINCOLN
ROUTE: 01972
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 4.87
YEAR BUILT: 1935

		TYPE OF SUPERSTRUCTURE =			
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM OR		NOT APPLICABLE		
		TYPE OF SUBSTRUCTURE =			
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTMEN				
BENTS:	CONCRETE COLUMN TWO POST BE				
PIERS:	NOT APPLICABLE	NI ON ROCK I CONDATION			
TILINO.	NOT AT LICABLE				
		SCOUR EVALUATION =			
	our critical; field review indicates the provide scour countermeasures.		red at bridge foundations. Immediate action are installed but they are needed.		
		INSPECTION PROCEDURES -			
What Initiated the Call-out Inspection? [] BridgeWatch Alert					
	·		al Maintenance Personnel		
		[] THP or Local Law Enf	forcement Personnel		
		[] Other:			
Things to c	heck on a bridge during floods:	<u>.</u>			
[] - Span	movement - horizontally as we	II as vertically			
1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck.					
2. 0	check for plumb of piers or ben	ts.	-		
[] - Check for embankment erosion					
[] - Chec					
[] - Check pier exposure, if possible, and compare to previous inspection					
[] - Review the latest bridge inspection report versus current field conditions					
	.	•			
If Closure is	recommended:				
 Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded. 					
[] - Conta	act: (1) District Maintenance Su	pervisor (if bridge is State	maintained)		
	(2) City or County Highway	Maintenance Official (if br	idge is not State maintained)		
	(3) Tennessee Highway Pa	trol and/or local law enforce	ement Officers as appropriate		
	(4) TDOT Regional Bridge I	Engineer			
] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.				

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	State District maintenance or local highway maintenance by bridge on the selected detour route shall be checked		
] - The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.			
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 433-3045		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 433-2585		
COUNTY SHERIFF'S OFFICE	(931) 433-3111		
The report shall include the date and time as appropriate, photographs of the bridge	- Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.		
COMMENTS:			
Suggested List of Equipment to conduct the Ins	pection:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricac	de Tape printed with the following message:		
SAFETY HAZARD K	FFP ΔWΔΥ		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

17-Apr-19