HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 520A4410001

BRIDGE OWNER: LINCOLN COUNTY

ROAD NAME: DRENNON RD

CROSSING: COLDWATER CREEK

LATITUDE:: N 35.04855 DEGREES

COUNTY: LINCOLN
ROUTE: 0A441
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.02
YEAR BUILT: 1975

LON	NGITUDE: W 86.67502 DEGREES	1	YEAR BUILT: 1975	
		TYPE OF SUPERSTRUCTURE		
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM O	R GIRDER APPR. SPAN:	NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE		
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	NT ON ROCK FOUNDATION		
BENTS:	NOT APPLICABLE			
PIERS:	NOT APPLICABLE			
ı		SCOUR EVALUATION		
Bridge has i	inknown foundations. Risk of sor		bridge shall be monitored for distress	
	icant flood events. No scour cou			
		INSPECTION PROCEDURES =		
What Initiated the Call-out Inspection?		[] BridgeWatch Alert		
	·	[] TDOT District or Loca	al Maintenance Personnel	
		[] THP or Local Law En	forcement Personnel	
		[] Other:		
Things to c	heck on a bridge during floods	<u>s:</u>		
[] - Span	movement - horizontally as w	ell as vertically		
1. 0	Check displacement / deflectio	n along curb line, both bridg	e rails and outer edge of bridge deck.	
2. 0	Check for plumb of piers or be	nts.		
[] - Chec	k for embankment erosion			
[] - Chec	k for drift build-up on piers or	bents		
[] - Chec	k pier exposure, if possible, ar	nd compare to previous insp	ection	
[] - Revie	ew the latest bridge inspection	report versus current field o	onditions	
lf Clasura is	racammandadı			
	recommended:			
Coun temp	nty or City Maintenance Persor	nnel. Use Barricade Tape, tra rists to stay off of the bridge	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may	
[] - Contact: (1) District Maintenance Supervisor (if bridge is State maintained)				
	(2) City or County Highwa	y Maintenance Official (if b	ridge is not State maintained)	
	` , , ,	•	ement Officers as appropriate	
	(4) TDOT Regional Bridge			
] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.			

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with State officials in establishing a detour route. Any brid prior to signing the detour route. 	District maintenance or local highway maintenance ge on the selected detour route shall be checked		
 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 			
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 433-3045		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 433-2585		
COUNTY SHERIFF'S OFFICE	(931) 433-3111		
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct the Inspection Latest Bridge Inspection Report	<u>n:</u>		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tap	e printed with the following message:		
SAFETY HAZARD KEEP A	WAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

17-Apr-19