## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 540A3870001
BRIDGE OWNER: McMINN COUNTY
ROAD NAME: CLAYHILL RD
CROSSING: OOSTANULA CREEK

LATITUDE:: N 35.37006 DEGREES
LONGITUDE: W 84.63653 DEGREES

COUNTY: McMINN
ROUTE: 0A387
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 2.26
YEAR BUILT: 1973

		TYPE OF SUPERSTRUCTURE =		
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM OR		NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE =		
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTMEN	IT ON UNKNOWN FOUNDATION		
BENTS:	CONCRETE COLUMN FOUR OR MOR	R OR MORE POST BENT ON UNKNOWN FOUNDATION		
PIERS:	NOT APPLICABLE			
		SCOUR EVALUATION =		
Deider has t	unluncium forum deticum. Diele ef con		huidee ahall ha maasitanad fan distussa	
	inknown foundations. Risk of scolicant flood events. Monitor bridge		bridge shall be monitored for distress termeasures.	
		INSPECTION PROCEDURES -		
What Initiat				
•		[ ] BridgeWatch Alert [ ] TDOT District or Loca	al Maintenance Personnel	
		[ ] THP or Local Law Enf		
		• •		
Things to c	heck on a bridge during floods	<u>.</u>		
[ ] - Span	movement - horizontally as we	ell as vertically		
	•	•	e rails and outer edge of bridge deck.	
	Check for plumb of piers or ben			
[ ] - Chec	k for embankment erosion			
[ ] - Chec	k for drift build-up on piers or b	pents		
[ ] - Chec	k pier exposure, if possible, an	d compare to previous inspe	ection	
[ ] - Review the latest bridge inspection report versus current field conditions				
		•		
<u>If Closure is</u>	recommended:			
Coun temp	- Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.			
[ ] - Conta	act: (1) District Maintenance Su	upervisor ( if bridge is State	maintained )	
	(2) City or County Highway	Maintenance Official (if br	idge is not State maintained )	
	(3) Tennessee Highway Pa	trol and/or local law enforce	ement Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer		
	- The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.			

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	te District maintenance or local highway maintenance idge on the selected detour route shall be checked		
[ ] - The bridge can be re-opened only after a TDO units and they are determined to be structural	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(423) 745-7634		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(423) 745-1820		
COUNTY SHERIFF'S OFFICE	(423) 745-5620		
The report shall include the date and time of the as appropriate, photographs of the bridge and	- Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.		
COMMENTS:			
Suggested List of Equipment to conduct the Inspect Latest Bridge Inspection Report Scour POA Report with the above Checklist	tion:		
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole	and and the Lord of the College Co.		
A 1000 Foot Roll of yellow Polyethylene Barricade Ta			

TDOT radio directory (State Personnel only)

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape