HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 54SR0390001

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: HWY 39

CROSSING: MIDDLE CREEK

LATITUDE:: N 35.42591 DEGREES LONGITUDE: W 84.51554 DEGREES

COUNTY: McMINN
ROUTE: SR039
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 13.35
YEAR BUILT: 1951

		TYPE OF SUPERSTRUCTURE =	
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE -	
ABUTMENTS:	CONCRETE SPILL THROUGH ABUT	MENT ON TIMBER PILE FOUNDATION	N
BENTS:	CONCRETE COLUMN TWO POST BI	ENT ON TIMBER PILE FOUNDATION	ı
PIERS:	CONCRETE COLUMNS WITH SOLID	WEB WALL (DUMB BELL) ON TIME	BER PILE FOUNDATION
		SCOUR EVALUATION -	
•	our critical; bridge foundations de ling scour countermeasures.	termined to be unstable for cald	culated scour conditions. Monitor bridge in
		INSPECTION PROCEDURES -	
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert	
	•		I Maintenance Personnel
		[] THP or Local Law Enf	orcement Personnel
		[] Other:	
1. 0 2. 0 [] - Chec [] - Chec	movement - horizontally as we Check displacement / deflection Check for plumb of piers or ber k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, an ew the latest bridge inspection	n along curb line, both bridge nts. bents d compare to previous inspe	
If Closure is	recommended:		
Cour temp] - Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.		
[] - Conta	act: (1) District Maintenance S	upervisor (if bridge is State	maintained)
	(2) City or County Highwa	y Maintenance Official (if br	idge is not State maintained)
	(3) Tennessee Highway Pa	atrol and/or local law enforce	ment Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
	e Bridge should remain closed until the water recedes and a daylight visual inspection is made a TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	n State District maintenance or local highway maintenance ny bridge on the selected detour route shall be checked		
	 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(423) 290-7467		
DISTRICT MAINTENANCE SUPERVISOR	(423) 290-7491		
TENNESSEE HIGHWAY PATROL	(423) 634-6898		
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 			
COMMENTS:			
Suggested List of Equipment to conduct the Ins	spection:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barrica	de Tape printed with the following message:		
SAFETY HAZARD K	(EEP AWAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)