## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 550A4940001
BRIDGE OWNER: TOWN OF SELMER
ROAD NAME: RAILROAD ST
CROSSING: CYPRESS CREEK

LATITUDE:: N 35.16992 DEGREES
LONGITUDE: W 88.58814 DEGREES

COUNTY: McNAIRY
ROUTE: 0A494
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.20
YEAR BUILT: 1985

20.	1011052. 11 00.00014 5201121			12/11/201211 1000		
		TYPE OF SUP	ERSTRUCTURE -			
MAIN SPAN:	PRESTRESSED CONCRETE - BOX GIRDERS - SINGLE OR SPREAD	BEAM OR	APPR. SPAN:	NOT APPLICABLE		
		TYPE OF SU	BSTRUCTURE -			
ABUTMENTS:	CONCRETE STUB ABUTMENT ON	RETE STUB ABUTMENT ON CONCRETE PILE FOUNDATION				
BENTS:	NOT APPLICABLE					
PIERS:	CONCRETE HAMMERHEAD PIER ON CONCRETE PILE FOUNDATION					
		SCOUR E	VALUATION =			
	unknown foundations. Risk of scr icant flood events. Monitor bridg			bridge shall be monitored for distress termeasures.		
		<ul><li>INSPECTION</li></ul>	PROCEDURES =			
What Initiat	ed the Call-out Inspection?	[ ] Bridg	eWatch Alert			
		[ ] TDOT	District or Loca	al Maintenance Personnel		
		[ ] THP (	or Local Law Ent	forcement Personnel		
		[ ] Other	:			
_	heck on a bridge during flood					
1. (	-	n along curb	-	e rails and outer edge of bridge deck.		
	Check for plumb of piers or be	nts.				
	k for embankment erosion	h anda				
	k for drift build-up on piers or					
	[ ] - Check pier exposure, if possible, and compare to previous inspection [ ] - Review the latest bridge inspection report versus current field conditions					
[ ] - Revie	ew the latest bridge inspection	report versu	s current field c	onations		
lf Closure is	recommended:					
Coun temp	nty or City Maintenance Person	nnel. Use Bar rists to stay o	ricade Tape, traf	eured and properly closed by District, ific cones and/or traffic flares as until such time as the bridge may		
[ ] - Conta	act: (1) District Maintenance S	Supervisor (i	f bridge is State	maintained )		
	(2) City or County Highwa	y Maintenand	ce Official (if br	idge is not State maintained )		
	(3) Tennessee Highway P	atrol and/or le	ocal law enforce	ment Officers as appropriate		
	(4) TDOT Regional Bridge	Engineer				
	<ul> <li>The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.</li> </ul>					

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	lishing a detour route. Any bri	te District maintenance or local highway maintenance idge on the selected detour route shall be checked			
[ ] - The bridge can b units and they ar	<ul> <li>The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.</li> </ul>				
CONTACT PERSONN	IEL:	TELEPHONE NUMBER:			
CITY MAYOR'S OFFI	CE	(731) 645-3241			
POLICE OFFICE		(731) 645-7907			
PUBLIC WORKS DIR	ECTOR	(731) 645-7928			
The report shall i as appropriate, p	- Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.				
COMMENTS:					
Suggested List of Equi Latest Bridge Inspection Scour POA Report with Bridge Design Plans, if	the above Checklist	ion:			
Tape measure with wei					
Plumb bob					
Range Pole					
A 1000 Foot Roll of yell	• •	ape printed with the following message:			
	SAFETY HAZARD KEED				

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)