HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 56020960001

BRIDGE OWNER: MACON COUNTY

ROAD NAME: HANESTOWN RD

CROSSING: LONG CREEK

LATITUDE:: N 36.62362 DEGREES
LONGITUDE: W 86.11120 DEGREES

COUNTY: MACON
ROUTE: 02096
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 1.38
YEAR BUILT: 1975

LON	NGITUDE: W 86.11120 DEGREE	S	YEAR BUILT: 1975	
MAIN SPAN:	PRESTRESSED CONCRETE CONT STRINGER/MULTI-BEAM OR GIRD		NOT APPLICABLE	
-		TYPE OF SUBSTRUCTURE		
ABUTMENTS: BENTS:	CONCRETE FULL HEIGHT ABUTM NOT APPLICABLE	ENT ON CONCRETE SPREAD FOOTI	NG FOUNDATION	
PIERS:	CONCRETE HAMMERHEAD PIER ON CONCRETE SPREAD FOOTING FOUNDATION			
		SCOUR EVALUATION		
during signif			bridge shall be monitored for distress in fair condition. Some minor repairs to the	
		 INSPECTION PROCEDURES 		
What Initiated the Call-out Inspection?		[] BridgeWatch Alert		
		• •	al Maintenance Personnel	
		[] THP or Local Law En		
		[] Other:		
Things to c	heck on a bridge during flood	le•		
1. C 2. C [] - Chec [] - Chec	movement - horizontally as well- check displacement / deflection check for plumb of piers or be k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, a ew the latest bridge inspection	on along curb line, both bridgents. bents dents dente dente		
If Closure is	recommended:			
Coun temp	nty or City Maintenance Perso	nnel. Use Barricade Tape, tra rists to stay off of the bridge	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may	
[] - Conta	act: (1) District Maintenance	Supervisor (if bridge is State	maintained)	
	(2) City or County Highwa	ay Maintenance Official (if b	ridge is not State maintained)	
	(3) Tennessee Highway F	Patrol and/or local law enforce	ement Officers as appropriate	
	(4) TDOT Regional Bridge	e Engineer		
	Bridge should remain closed เ TDOT bridge inspection team		daylight visual inspection is made	

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



officials in establishing a detour route. Any brid prior to signing the detour route.	ge on the selected detour route shall be checked
[] - The bridge can be re-opened only after a TDOT units and they are determined to be structurally	
CONTACT PERSONNEL:	TELEPHONE NUMBER:
COUNTY MAYOR'S OFFICE	(615) 666-2363
HWY. CHIEF ADMINISTRATOR'S OFFICE	(615) 666-3910
COUNTY SHERIFF'S OFFICE	(615) 666-3325
as appropriate, photographs of the bridge and so scouring has occurred, the report shall also be comments:	copied to Bridge Inspection Headquarters.
-	
Suggested List of Equipment to conduct the Inspectio Latest Bridge Inspection Report	<u>n:</u>
Scour POA Report with the above Checklist	
Bridge Design Plans, if available	
Tape measure with weight	
Plumb bob	
Range Pole	
A 1000 Foot Roll of yellow Polyethylene Barricade Tap SAFETY HAZARD KEEP A	
A Barricade Tape Dispenser with serrated cutter	
A roll of Duct Tape	
Traffic Cones - Minimum of four (4)	
Traffic Safety Flares - Minimum of four (4) or set of ele	ectronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)