HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 57015810023
BRIDGE OWNER: MADISON COUNTY
ROAD NAME: CHRISTMASVILLE RD
CROSSING: DUFFY'S CREEK

LATITUDE:: N 35.76686 DEGREES LONGITUDE: W 88.73772 DEGREES

COUNTY: MADISON
ROUTE: 00872
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 10.01
YEAR BUILT: 1951

		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	CONCRETE - BOX BEAM OR GIRDE		
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	TIMBER CAP ON TIMBER PILE FOU	NDATION	
BENTS:	TIMBER PILE BENT ON PILE FOUN	DATION	
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION	
Bridge is sc	our critical: bridge foundations de	etermined to be unstable for calculated scour conditions. No scour	
	sures are installed but they are n		
		- INSPECTION PROCEDURES -	
What Initiat	ted the Call-out Inspection?	[] BridgeWatch Alert	
That initiated the can cat inspection.		[] TDOT District or Local Maintenance Personnel	
		[] THP or Local Law Enforcement Personnel	
		[] Other:	
Things to c	heck on a bridge during floods	<u>s:</u>	
[] - Span	movement - horizontally as w	ell as vertically	
	•	n along curb line, both bridge rails and outer edge of bridge deck.	
	Check for plumb of piers or be		
[] - Chec	k for embankment erosion		
[] - Chec	k for drift build-up on piers or	bents	
[] - Chec	k pier exposure, if possible, ar	nd compare to previous inspection	
[] - Review the latest bridge inspection report versus current field conditions			
If Closure is	s recommended:		
Cour temp	nty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may	
[] - Cont	act: (1) District Maintenance S	Supervisor (if bridge is State maintained)	
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)	
	(3) Tennessee Highway Pa	atrol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer	
] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	State District maintenance or local highway maintenance by bridge on the selected detour route shall be checked	
] - The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:	
COUNTY MAYOR'S OFFICE	(731) 423-6020	
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 422-1651	
COUNTY SHERIFF'S OFFICE	(731) 423-6000	
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 		
COMMENTS:		
Suggested List of Equipment to conduct the Insp	ection:	
Latest Bridge Inspection Report Scour POA Report with the above Checklist		
Bridge Design Plans, if available		
Tape measure with weight		
Plumb bob		
Range Pole		
A 1000 Foot Roll of yellow Polyethylene Barricade	e Tape printed with the following message:	
SAFETY HAZARD KE		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24