HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 57016440013
BRIDGE OWNER: CITY OF JACKSON
ROAD NAME: WESTOVER RD
CROSSING: OVERFLOW

LATITUDE:: N 35.61408 DEGREES LONGITUDE: W 88.86267 DEGREES

COUNTY: MADISON
ROUTE: 0A980
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.73
YEAR BUILT: 1922

		TYPE OF SUPERSTRUCTURE -			
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN:	NOT APPLICABLE		
		TYPE OF SUPSTRUCTURE —			
ARI ITMENTS:	CONCRETE FULL HEIGHT ABUTMEN	TYPE OF SUBSTRUCTURE =			
BENTS:					
	CONCRETE PILE BENT ON PILE FOU	DINDATION			
PIERS:	NOT APPLICABLE				
		SCOUR EVALUATION -			
	inknown foundations. Risk of sco icant flood events. Monitor bridge		bridge shall be monitored for distress termeasures.		
		INSPECTION PROCEDURES -			
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert			
Wildt IIIItiat	ed the dan dat mopeonom.		Il Maintenance Personnel		
		[] THP or Local Law Enf			
			ordenient i ersonner		
		[] Other.			
Things to c	heck on a bridge during floods				
Things to check on a bridge during floods:					
 Span movement - horizontally as well as vertically Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck. 					
	<u>-</u>		rails and outer edge of bridge deck.		
2. Check for plumb of piers or bents.					
[] - Check for embankment erosion					
	[] - Check for drift build-up on piers or bents				
[] - Check pier exposure, if possible, and compare to previous inspection					
[] - Review the latest bridge inspection report versus current field conditions					
lf Claarina ia					
	recommended:				
 Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded. 					
[] - Conta	maintained)				
	(2) City or County Highway	Maintenance Official (if br	idge is not State maintained)		
	(3) Tennessee Highway Pa	trol and/or local law enforce	ment Officers as appropriate		
	(4) TDOT Regional Bridge	Engineer	-		
	 The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team. 				

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route. 			
	he bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
CITY MAYOR'S OFFICE	(731) 425-8240		
CITY ENGINEER'S OFFICE	(731) 425-8219		
POLICE OFFICE	(731) 425-8465		
PUBLIC WORKS DIRECTOR	(731) 425-8535		
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. COMMENTS:			
Suggested List of Equipment to conduct the Inspection	<u>n:</u>		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole A 1000 Foot Boll of vollow Bolyothylone Barriagde Ton	a printed with the following massage:		
A 1000 Foot Roll of yellow Polyethylene Barricade Tap SAFETY HAZARD KEEP A			

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24