HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



COUNTY: MADISON

ROUTE: 00877

BRIDGE ID NUMBER: 57S81820007
BRIDGE OWNER: MADISON COUNTY
ROAD NAME: OLD MEDINA RD
CROSSING: BRANCH

LATITUDE:: N 35.74247 DEGREES
LONGITUDE: W 88.79269 DEGREES

SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 7.76
YEAR BUILT: 2001

TYPE OF SUPERSTRUCTURE MAIN SPAN-**CONCRETE - CHANNEL BEAM** APPR. SPAN: NOT APPLICABLE TYPE OF SUBSTRUCTURE ABUTMENTS: CONCRETE STUB ABUTMENT ON CONCRETE PILE FOUNDATION BENTS: **CONCRETE PILE BENT ON PILE FOUNDATION** PIERS: **NOT APPLICABLE** SCOUR EVALUATION Bridge has unknown foundations. Risk of scour cannot be determined. The bridge shall be monitored for distress during significant flood events. Monitor bridge in lieu of installing scour countermeasures. **INSPECTION PROCEDURES** [] BridgeWatch Alert What Initiated the Call-out Inspection? [1 TDOT District or Local Maintenance Personnel [] THP or Local Law Enforcement Personnel [] Other: Things to check on a bridge during floods: [] - Span movement - horizontally as well as vertically 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck. 2. Check for plumb of piers or bents. [] - Check for embankment erosion [] - Check for drift build-up on piers or bents [] - Check pier exposure, if possible, and compare to previous inspection [] - Review the latest bridge inspection report versus current field conditions If Closure is recommended: [] - Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded. [] - Contact: (1) District Maintenance Supervisor (if bridge is State maintained) (2) City or County Highway Maintenance Official (if bridge is not State maintained) (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate

PUBLICATION DATE

(4) TDOT Regional Bridge Engineer

by a TDOT bridge inspection team.

[] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	State District maintenance or local highway maintenance by bridge on the selected detour route shall be checked
[] - The bridge can be re-opened only after a Ti units and they are determined to be structu	DOT bridge inspection team checks the substructure urally stable.
CONTACT PERSONNEL:	TELEPHONE NUMBER:
COUNTY MAYOR'S OFFICE	(731) 423-6020
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 422-1651
COUNTY SHERIFF'S OFFICE	(731) 423-6000
The report shall include the date and time o as appropriate, photographs of the bridge a	spection to BridgeWatch scour monitoring system. If the inspection, a brief summary of findings and, and stream channel measurements. If significant be be copied to Bridge Inspection Headquarters.
COMMENTS:	
Suggested List of Equipment to conduct the Insp	ection:
Latest Bridge Inspection Report Scour POA Report with the above Checklist	
Bridge Design Plans, if available	
Tape measure with weight	
Plumb bob	
Range Pole	
A 1000 Foot Roll of yellow Polyethylene Barricade	e Tape printed with the following message:
SAFETY HAZARD KE	

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24