## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 57\$R0010003

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: US70

CROSSING: ROBERTSON CREEK

LATITUDE:: N 35.60658 DEGREES
LONGITUDE: W 89.02456 DEGREES

COUNTY: MADISON
ROUTE: SR001
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 3.44
YEAR BUILT: 1925

LON	NGHODE. W 69.02436 DEGREES	TEAN BOILT. 1923		
		TYPE OF SUPERSTRUCTURE		
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN: NOT APPLICABLE		
		TYPE OF SUBSTRUCTURE		
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	NT ON SOIL FOUNDATION		
BENTS:	CONCRETE PILE BENT ON PILE FO	NCRETE PILE BENT ON PILE FOUNDATION		
PIERS:	NOT APPLICABLE			
		SCOUR EVALUATION		
•	our critical; bridge foundations de sures are installed but they are r	termined to be unstable for calculated scour conditions. No scour eeded.		
		INSPECTION PROCEDURES		
What Initiated the Call-out Inspection		[ ] BridgeWatch Alert		
	·	[ ] TDOT District or Local Maintenance Personnel		
		[ ] THP or Local Law Enforcement Personnel		
		[ ] Other:		
1. C 2. C [ ] - Chec [ ] - Chec [ ] - Chec	Check for plumb of piers or be k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, a	along curb line, both bridge rails and outer edge of bridge deck. ts.		
f Closure is	recommended:			
Coun temp	nty or City Maintenance Person	ross road until bridge is secured and properly closed by District, nel. Use Barricade Tape, traffic cones and/or traffic flares as sts to stay off of the bridge until such time as the bridge may		
[ ] - Conta	act: (1) District Maintenance S	upervisor ( if bridge is State maintained )		
	(2) City or County Highwa	Maintenance Official (if bridge is not State maintained)		
	(3) Tennessee Highway P	trol and/or local law enforcement Officers as appropriate		
	(4) TDOT Regional Bridge	Engineer		
	<ul> <li>The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.</li> </ul>			

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



] - The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route.			
[ ] - The bridge can be re-opened only after a TDO units and they are determined to be structura	<ul> <li>The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.</li> </ul>		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(731) 234-9561		
DISTRICT MAINTENANCE SUPERVISOR	(731) 694-6673		
TENNESSEE HIGHWAY PATROL	(731) 423-6635		
<ul> <li>Summarize and submit findings from the inspection to BridgeWatch scour monitoring system.</li> <li>The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.</li> </ul>			
COMMENTS:			
Suggested List of Equipment to conduct the Inspec Latest Bridge Inspection Report Scour POA Report with the above Checklist Bridge Design Plans, if available Tape measure with weight Plumb bob	tion:		
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade T	ape printed with the following message:		

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

**SAFETY HAZARD KEEP AWAY** 

TDOT two-way radio (State Personnel only) and/or cellular telephone

**TDOT radio directory (State Personnel only)**