HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 57\$R0010029

BRIDGE OWNER: STATE OF TENNESSEE ROAD NAME: WHITEHALL ST

CROSSING: GILMERS CREEK

LATITUDE:: N 35.74142 DEGREES LONGITUDE: W 88.70131 DEGREES

COUNTY: MADISON
ROUTE: SR001
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 27.41
YEAR BUILT: 1926

LON	GITUDE: W 88.70131 DEGREES	YEAR BUILT: 1926		
		TYPE OF SUPERSTRUCTURE		
MAIN SPAN:	PRESTRESSED CONCRETE - BOX E GIRDERS - MULTIPLE	BEAM OR APPR. SPAN: NOT APPLICABLE		
		TYPE OF SUBSTRUCTURE		
ABUTMENTS:	CONCRETE STUB ABUTMENT ON T	IMBER PILE FOUNDATION		
BENTS:	NOT APPLICABLE			
PIERS:	CONCRETE COLUMNS WITH SOLID	WEB WALL (DUMB BELL) ON TIMBER PILE FOUNDATION		
		SCOUR EVALUATION		
event. Deteri		have been installed to reduce the risk of bridge failure during a flood riprap should be reported to TDOT for assessment. Rip-rap protection has		
		INSPECTION PROCEDURES		
What Initiated the Call-out Inspection?		[] BridgeWatch Alert		
		[] TDOT District or Local Maintenance Personnel		
		[] THP or Local Law Enforcement Personnel		
		[] Other:		
Things to cl	heck on a bridge during floods			
_				
	movement - horizontally as we	ell as vertically n along curb line, both bridge rails and outer edge of bridge deck.		
	Check for plumb of piers or ber			
	k for embankment erosion			
	[] - Check for drift build-up on piers or bents			
	[] - Check pier exposure, if possible, and compare to previous inspection			
	[] - Review the latest bridge inspection report versus current field conditions			
		•		
If Closure is	recommended:			
Coun temp	ty or City Maintenance Person	cross road until bridge is secured and properly closed by District, nel. Use Barricade Tape, traffic cones and/or traffic flares as ists to stay off of the bridge until such time as the bridge may		
[] - Conta	act: (1) District Maintenance S	upervisor (if bridge is State maintained)		
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)		
	(3) Tennessee Highway Pa	atrol and/or local law enforcement Officers as appropriate		
	(4) TDOT Regional Bridge	Engineer		
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.			

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	 The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route. The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(731) 234-9561		
DISTRICT MAINTENANCE SUPERVISOR	(731) 694-6673		
TENNESSEE HIGHWAY PATROL	(731) 423-6635		
[] - Summarize and submit findings from the inspecting The report shall include the date and time of the inspection as appropriate, photographs of the bridge and structured in the second property of the second property in the se	inspection, a brief summary of findings and, ream channel measurements. If significant		
COMMENTS:			
Suggested List of Equipment to conduct the Inspection	<u>n:</u>		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tape	e printed with the following message:		
SAFETY HAZARD KEEP AV	WAY		
A Barricade Tape Dispenser with serrated cutter			
A roll of Duct Tape			
Traffic Cones - Minimum of four (4)			
Traffic Safety Flares - Minimum of four (4) or set of elec	ctronic warning flashers		

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)