HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 57\$R0050005

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: US45

CROSSING: BEAR CREEK

LATITUDE:: N 35.49169 DEGREES
LONGITUDE: W 88.72200 DEGREES

COUNTY: MADISON
ROUTE: SR005
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 1.50

LON	IGITUDE: W 88.72200 DEGREES	YEAR BUILT: 1928	
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN: NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON CO	DNCRETE PILE FOUNDATION	
BENTS:	CONCRETE PILE BENT ON PILE FOL	INDATION	
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION	
•	our critical; bridge foundations det stalled and is in good condition.	ermined to be unstable for calculated scour conditions. Rip-rap protection	
		INSPECTION PROCEDURES	
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert	
	·	[] TDOT District or Local Maintenance Personnel	
		THP or Local Law Enforcement Personnel	
		[] Other:	
[] - Span 1. C 2. C [] - Chec [] - Chec	Check for plumb of piers or ben k for embankment erosion k for drift build-up on piers or b k pier exposure, if possible, and	ll as vertically along curb line, both bridge rails and outer edge of bridge deck. ts.	
If Closure is	recommended:		
Coun temp	ity or City Maintenance Personi	ross road until bridge is secured and properly closed by District, nel. Use Barricade Tape, traffic cones and/or traffic flares as sts to stay off of the bridge until such time as the bridge may	
[] - Conta	act: (1) District Maintenance Su	pervisor (if bridge is State maintained)	
	(2) City or County Highway	Maintenance Official (if bridge is not State maintained)	
	(3) Tennessee Highway Pa	trol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer	
] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	th State District maintenance or local highway maintenance Any bridge on the selected detour route shall be checked		
[] - The bridge can be re-opened only after a units and they are determined to be stru	 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(731) 234-9561		
DISTRICT MAINTENANCE SUPERVISOR	(731) 694-6673		
TENNESSEE HIGHWAY PATROL	(731) 423-6635		
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct the In	nspection:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barrica	ade Tane printed with the following message:		
SAFETY HAZADD			

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24