HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 60018970003 BRIDGE OWNER: MAURY COUNTY ROAD NAME: HOWARD BRIDGE RD. CROSSING: DUCK RIVER

COUNTY: MAURY ROUTE: 01897 SPECIAL CASE: 0 COUNTY SEQUENCE: 1

	TITUDE:: N 35.57323 DEGREES NGITUDE: W 86.92213 DEGREES	LOG MILE: 2.53 YEAR BUILT: 1962	
	-	TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	STEEL CONTINUOUS - STRINGER/MI GIRDER	ULTI-BEAM OR APPR. SPAN: CONCRETE - TEE BEAM	
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE SPILL THROUGH ABUTN	MENT ON UNKNOWN FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	CONCRETE HAMMERHEAD PIER ON	ROCK FOUNDATION	
	-	SCOUR EVALUATION	
		ermined to be unstable for calculated scour conditions. Rip-rap protection ective. Major repair or replacement of the protection system is needed.	
		INSPECTION PROCEDURES ————————————————————————————————————	
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert	
		[] TDOT District or Local Maintenance Personnel	
		[] THP or Local Law Enforcement Personnel	
		[] Other:	
[] - Span 1. C 2. C [] - Chec [] - Chec	Check for plumb of piers or ben k for embankment erosion k for drift build-up on piers or b k pier exposure, if possible, and	Il as vertically along curb line, both bridge rails and outer edge of bridge deck. ts.	
If Closure is	recommended:		
Coun temp	nty or City Maintenance Personr	ross road until bridge is secured and properly closed by District, nel. Use Barricade Tape, traffic cones and/or traffic flares as sts to stay off of the bridge until such time as the bridge may	
[] - Conta] - Contact: (1) District Maintenance Supervisor (if bridge is State maintained)		
	(2) City or County Highway	Maintenance Official (if bridge is not State maintained)	
	(3) Tennessee Highway Pa	trol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge I	Engineer	
	- The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with State officials in establishing a detour route. Any bridge prior to signing the detour route. 	District maintenance or local highway maintenance ge on the selected detour route shall be checked		
	 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 375-1000		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 375-6202		
COUNTY SHERIFF'S OFFICE	(931) 380-5733		
[] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct the Inspection Latest Bridge Inspection Report	<u>n:</u>		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tape	e printed with the following message:		
CAEETY HAZARD VEED AT	M/AV		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24