## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 60SR0060025

BRIDGE OWNER: STATE OF TENNESSEE
ROAD NAME: NASHVILLE HWY.
CROSSING: DUCK RIVER

COUNTY: MAURY
ROUTE: SR007
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 13.90

	TITUDE:: N 35.62170 DEGREES	
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	STEEL CONTINUOUS - STRINGER/	
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	CONCRETE SPILL THROUGH ABUT	MENT ON ROCK FOUNDATION
BENTS:	CONCRETE COLUMN TWO POST E	BENT ON CONCRETE PILE FOUNDATION
PIERS:	CONCRETE SOLID SHAFT PIER ON	TIMBER PILE FOUNDATION
		SCOUR EVALUATION
		etermined to be unstable for calculated scour conditions. Rip-rap protection ignificant repairs to the protection system are needed.
		INSPECTION PROCEDURES
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert
	·	[ ] TDOT District or Local Maintenance Personnel
		[ ] THP or Local Law Enforcement Personnel
		[ ] Other:
_	heck on a bridge during flood movement - horizontally as w	
	•	n along curb line, both bridge rails and outer edge of bridge deck.
	Check for plumb of piers or be	nts.
	k for embankment erosion	
	k for drift build-up on piers or	
		nd compare to previous inspection
[ ] - Kevie	w the latest bridge inspection	report versus current field conditions
<u>If Closure is</u>	recommended:	
Coun temp	ity or City Maintenance Persoi	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may
[ ] - Conta	act: (1) District Maintenance S	Supervisor ( if bridge is State maintained )
	(2) City or County Highwa	y Maintenance Official ( if bridge is not State maintained )
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	•
	<ul> <li>The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.</li> </ul>	

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	with State District maintenance or local highway maintenance e. Any bridge on the selected detour route shall be checked	
] - The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:	
REGION BRIDGE ENGINEER	(615) 476-8860	
DISTRICT MAINTENANCE SUPERVISOR	(931) 205-6399	
TENNESSEE HIGHWAY PATROL	(931) 766-1425	
<ul> <li>- Summarize and submit findings from the inspection to BridgeWatch scour monitoring system.         The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.     </li> </ul>		
COMMENTS:		
Suggested List of Equipment to conduct the Latest Bridge Inspection Report	e Inspection:	
Scour POA Report with the above Checklist		
Bridge Design Plans, if available		
Tape measure with weight		
Plumb bob		
Range Pole		
	ricade Tape printed with the following message:	
SAFETY HAZAF	RD KEEP AWAY	

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24