HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



COUNTY: MAURY

ROUTE: SR007

BRIDGE ID NUMBER: 60SR0060026

BRIDGE OWNER: STATE OF TENNESSEE ROAD NAME: **NASHVILLE HWY.** CROSSING: DUCK RIVER

SPECIAL CASE: 0 COUNTY SEQUENCE: 1

	TITUDE:: N 35.62170 DEGREES LOG MILE: 13.90 NGITUDE: W 87.03420 DEGREES YEAR BUILT: 1947	
	TYPE OF SUPERSTRUCTURE -	
MAIN SPAN:	STEEL CONTINUOUS - STRINGER/MULTI-BEAM OR APPR. SPAN: CONCRETE - TEE BEAM GIRDER	
	TYPE OF SUBSTRUCTURE -	
ABUTMENTS:	CONCRETE SPILL THROUGH ABUTMENT ON ROCK FOUNDATION	
BENTS:	CONCRETE COLUMN TWO POST BENT ON CONCRETE PILE FOUNDATION	
PIERS:	CONCRETE SOLID SHAFT PIER ON TIMBER PILE FOUNDATION	
	SCOUR EVALUATION ————————————————————————————————————	
	our critical; bridge foundations determined to be unstable for calculated scour conditions. Rip-rap protection stalled but is in poor condition. Significant repairs to the protection system are needed.	
	INSPECTION PROCEDURES ————————————————————————————————————	
What Initiat	ed the Call-out Inspection? [] BridgeWatch Alert	
	[] TDOT District or Local Maintenance Personnel	
	[] THP or Local Law Enforcement Personnel	
	[] Other:	
[] - Span 1. C 2. C [] - Chec [] - Chec	heck on a bridge during floods: movement - horizontally as well as vertically Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck. Check for plumb of piers or bents. k for embankment erosion k for drift build-up on piers or bents k pier exposure, if possible, and compare to previous inspection we the latest bridge inspection report versus current field conditions	
If Closure is	recommended:	
Coun temp	at bridge with vehicle pulled across road until bridge is secured and properly closed by District, hty or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as orary measures to warn motorists to stay off of the bridge until such time as the bridge may operly closed and barricaded.	
[] - Conta	act: (1) District Maintenance Supervisor (if bridge is State maintained)	
	(2) City or County Highway Maintenance Official (if bridge is not State maintained)	
	(3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge Engineer	
] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.	

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	State District maintenance or local highway maintenance by bridge on the selected detour route shall be checked		
	 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(615) 476-8860		
DISTRICT MAINTENANCE SUPERVISOR	(931) 205-6399		
TENNESSEE HIGHWAY PATROL	(931) 766-1425		
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct the Insp Latest Bridge Inspection Report	ection:		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade			
SAFFTY HAZARD KE	EP AWAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24