HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



COUNTY: MONROE

BRIDGE ID NUMBER: 62012060003 BRIDGE OWNER: MONROE COUNTY ROAD NAME: OLD HWY 68 CROSSING: BRANCH

LATITUDE:: N 35.57260 DEGREES

ROUTE: 01206 SPECIAL CASE: 0 COUNTY SEQUENCE: 1 LOG MILE: 3.86

LON	NGITUDE: W 84.41870 DEGREES		YEAR BUILT: 1937
		TYPE OF SUPERSTRUCTURE =	
MAIN SPAN:	CONCRETE CONTINUOUS - CULVER FRAME CULVERTS)	T (INCLUDES APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE -	
ABUTMENTS:	CONCRETE BOX TYPE ON CONCRE	TE SPREAD FOOTING FOUNDATIO	N .
BENTS:	NOT APPLICABLE		
PIERS:	PIER WALL FOR CONCRETE BOX O	N CONCRETE SPREAD FOOTING F	OUNDATION
		SCOUR EVALUATION =	
	unknown foundations. Risk of sco iicant flood events. Monitor bridge	ur cannot be determined. The	bridge shall be monitored for distress termeasures.
		INSPECTION PROCEDURES =	
What Initiated the Call-out Inspection		[] BridgeWatch Alert	
		[] TDOT District or Loca	al Maintenance Personnel
		[] THP or Local Law Enf	forcement Personnel
		[] Other:	
1. 0 2. 0 [] - Chec [] - Chec [] - Chec	movement - horizontally as we Check displacement / deflection Check for plumb of piers or ben ok for embankment erosion ok for drift build-up on piers or b ok pier exposure, if possible, an ew the latest bridge inspection	along curb line, both bridge ts. pents d compare to previous inspe	
If Closure is	recommended:		
Coun temp	nty or City Maintenance Person	nel. Use Barricade Tape, traf	eured and properly closed by District, ific cones and/or traffic flares as until such time as the bridge may
[] - Contact: (1) District Maintenance Supervisor (if bridge is State maintained)			
	(2) City or County Highway	Maintenance Official (if br	idge is not State maintained)
	(3) Tennessee Highway Pa	trol and/or local law enforce	ment Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



officials in es		State District maintenance or local highway maintenance y bridge on the selected detour route shall be checked	
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERS	ONNEL:	TELEPHONE NUMBER:	
COUNTY MAYOR	'S OFFICE	(423) 442-3981	
HWY. CHIEF ADI	MINISTRATOR'S OFFICE	(423) 442-4569	
COUNTY SHERIF	F'S OFFICE	(423) 442-3911	
The report sha as appropriate	all include the date and time of the bridge and time of the bridge and the bridge are the bridge at the bridge are the bridge	nspection to BridgeWatch scour monitoring system. of the inspection, a brief summary of findings and, and stream channel measurements. If significant o be copied to Bridge Inspection Headquarters.	
COMMENTS:			
	quipment to conduct the Insp	pection:	
Latest Bridge Inspec	ction Report vith the above Checklist		
Bridge Design Plans			
Tape measure with			
Plumb bob			
Range Pole			
_	ellow Polyethylene Barricad	le Tape printed with the following message:	
•	SAFETY HAZARD KI		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24