HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



COUNTY: MONROE

BRIDGE ID NUMBER: 620A0670001
BRIDGE OWNER: MONROE COUNTY

ROAD NAME: OLD SWEETWATER CHURCH RD

CROSSING: SWEETWATER CREEK

LATITUDE:: N 35.64955 DEGREES

LONGITUDE: W 84.42810 DEGREES

ROUTE: 0A067
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.17

LON	IGITUDE: W 84.42810 DEGREES		YEAR BUILT: 1965
		TYPE OF SUPERSTRUCTURE -	
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM OF	GIRDER APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE =	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTMEN	IT ON CONCRETE SPREAD FOOTI	NG FOUNDATION
BENTS:	NOT APPLICABLE		
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION -	
event. Deter			the risk of bridge failure during a flood DOT for assessment. Rip-rap protection has
		INSPECTION PROCEDURES =	
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert	
			al Maintenance Personnel
		[] THP or Local Law En	
		[] •	
Things to c	heck on a bridge during floods	<u>.</u>	
[] - Snan	movement - horizontally as we	II as vertically	
	•	•	e rails and outer edge of bridge deck.
	Check for plumb of piers or ben		o rano ana cator cago or smago acon
	k for embankment erosion		
	k for drift build-up on piers or k	nents	
	k pier exposure, if possible, an		ection
	ew the latest bridge inspection		
[] Novice	The latest bridge inspection	oport versus current neia c	
If Closure is	recommended:		
Coun	ity or City Maintenance Person	nel. Use Barricade Tape, tra	cured and properly closed by District, ffic cones and/or traffic flares as
	orary measures to warn motori operly closed and barricaded.	sts to stay off of the bridge	until such time as the bridge may
[] - Conta	act: (1) District Maintenance Su	pervisor (if bridge is State	maintained)
	• •	•	ridge is not State maintained)
		•	ement Officers as appropriate
	(4) TDOT Regional Bridge		
[] - The E	` '	_	daylight visual inspection is made
	TDOT bridge inspection team.		,

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	ng a detour route. Any bridg	District maintenance or local highway maintenance ge on the selected detour route shall be checked		
[] - The bridge can be re- units and they are de	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.			
CONTACT PERSONNEL:		TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFIC	E	(423) 442-3981		
HWY. CHIEF ADMINISTRA	TOR'S OFFICE	(423) 442-4569		
COUNTY SHERIFF'S OFFI	CE	(423) 442-3911		
The report shall inclu as appropriate, photo	 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 			
COMMENTS:				
Suggested List of Equipme Latest Bridge Inspection Re Scour POA Report with the	•	<u>1:</u>		
Bridge Design Plans, if ava	ilable			
Tape measure with weight				
Plumb bob				
Range Pole				
A 1000 Foot Roll of yellow I	•	e printed with the following message:		
	SAFETY HAZARD KEED AV	$N\Delta V$		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24