## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 62SR0330001

BRIDGE OWNER: CITY OF MADISONVILLE

ROAD NAME: WARREN ST

CROSSING: MADISONVILLE BRANCH
LATITUDE:: N 35.51972 DEGREES
LONGITUDE: W 84.36053 DEGREES

ROUTE: 01210
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.12
YEAR BUILT: 1930

COUNTY: MONROE

201	1011052. 11 04.0000		12/11/20121. 1000	
-		TYPE OF SUPERSTRUCTU	RE ———	
MAIN SPAN:	CONCRETE CONTINUOUS - CULVE FRAME CULVERTS)	ERT (INCLUDES APPR. S	SPAN: NOT APPLICABLE	
		TYPE OF SUBSTRUCTUR	E	
ABUTMENTS:	CONCRETE BOX TYPE ON CONCR	ICRETE BOX TYPE ON CONCRETE SPREAD FOOTING FOUNDATION		
BENTS:	NOT APPLICABLE			
PIERS: PIER WALL FOR CONCRETE BOX ON CONCRETE SPREAD FOOTING FOUNDATION		TING FOUNDATION		
		SCOUR EVALUATION		
	unknown foundations. Risk of sc icant flood events. Monitor bridg		I. The bridge shall be monitored for distress r countermeasures.	
		INSPECTION PROCEDURE	ES <del></del>	
What Initiated the Call-out Inspection?		[ ] BridgeWatch Ale	ert	
		[ ] TDOT District or	r Local Maintenance Personnel	
		[ ] THP or Local La	w Enforcement Personnel	
		[ ] Other:		
Things to c	heck on a bridge during flood	le•		
_				
	movement - horizontally as w		bridge rails and outer edge of bridge deck.	
	Check displacement / deflection	<u> </u>	bridge rails and outer edge of bridge deck.	
	k for embankment erosion	:iit3.		
	k for drift build-up on piers or	· hents		
	k pier exposure, if possible, a		inspection	
	ew the latest bridge inspection	•	-	
[ ] Novic	, w the latest bridge mopeoner	Troport versus current in		
	recommended:			
Coun temp	nty or City Maintenance Person	nnel. Use Barricade Taporists to stay off of the br	is secured and properly closed by District, e, traffic cones and/or traffic flares as ridge until such time as the bridge may	
[ ] - Conta	act: (1) District Maintenance S	Supervisor (if bridge is	State maintained )	
	(2) City or County Highwa	ay Maintenance Official	( if bridge is not State maintained )	
	(3) Tennessee Highway P	atrol and/or local law en	nforcement Officers as appropriate	
	(4) TDOT Regional Bridge	e Engineer		
	he Bridge should remain closed until the water recedes and a daylight visual inspection is made y a TDOT bridge inspection team.			

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	ate District maintenance or local highway maintenance oridge on the selected detour route shall be checked		
<ul> <li>The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.</li> </ul>			
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
CITY MAYOR'S OFFICE	(423) 442-9416		
POLICE OFFICE	(423) 442-2268		
•	the inspection, a brief summary of findings and, d stream channel measurements. If significant		
COMMENTS:			
Suggested List of Equipment to conduct the Inspec	ction:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade			
SAFETY HAZARD KEE	PAWAY		
A Barricade Tape Dispenser with serrated cutter			
A roll of Duct Tape			
Traffic Cones - Minimum of four (4)			
Traffic Safety Flares - Minimum of four (4) or set of	_		
TDOT two-way radio (State Personnel only) and/or	cellular telephone		

**TDOT radio directory (State Personnel only)**