HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



COUNTY: MONTGOMERY

BRIDGE ID NUMBER: 630A3060001

BRIDGE OWNER: MONTGOMERY COUNTY
ROAD NAME: CHARLES HOLT RD
CROSSING: PASSENGER CREEK
LATITUDE:: N 36.50583 DEGREES
LONGITUDE: W 87.13702 DEGREES

ROUTE: 0A306 SPECIAL CASE: 0 COUNTY SEQUENCE: 1 LOG MILE: 0.08 YEAR BUILT: 1986

		TYPE OF SUPERSTRUCTURE =		
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM OF		NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE -		
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTMEN	NT ON CONCRETE SPREAD FOOTIN	NG FOUNDATION	
BENTS:	NOT APPLICABLE			
PIERS:	NOT APPLICABLE			
		SCOUR EVALUATION -		
Dridge beer	unknown foundations. Disk of oos		oridge shall be manitored for distress	
	icant flood events. Monitor bridge		oridge shall be monitored for distress termeasures.	
		INSPECTION PROCEDURES -		
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert		
			I Maintenance Personnel	
		[] THP or Local Law Enf	orcement Personnel	
		[] Other:		
Things to c	<u>heck on a bridge during floods</u>	<u>.</u>		
[] - Span	movement - horizontally as we	ell as vertically		
			rails and outer edge of bridge deck.	
	Check for plumb of piers or ben			
[] - Chec	k for embankment erosion			
[] - Chec	k for drift build-up on piers or b	pents		
[] - Chec	k pier exposure, if possible, an	d compare to previous inspe	ection	
[] - Review the latest bridge inspection report versus current field conditions				
<u>If Closure is</u>	recommended:			
Coun temp	nty or City Maintenance Person	nel. Use Barricade Tape, traf	ured and properly closed by District, fic cones and/or traffic flares as until such time as the bridge may	
[] - Conta	act: (1) District Maintenance So	upervisor (if bridge is State	maintained)	
	(2) City or County Highway	Maintenance Official (if bri	idge is not State maintained)	
	(3) Tennessee Highway Pa	trol and/or local law enforce	ment Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer		
	- The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.			

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



officials in e		State District maintenance or local highway maintenance y bridge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.			
CONTACT PER	SONNEL:	TELEPHONE NUMBER:		
COUNTY MAYO	PR'S OFFICE	(931) 648-5787		
HWY. CHIEF AL	DMINISTRATOR'S OFFICE	(931) 648-5740		
COUNTY SHER	IFF'S OFFICE	(931) 648-0611		
The report sh as appropria] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:				
Latest Bridge Inspe	Equipment to conduct the Inspection Report with the above Checklist	pection:		
Bridge Design Plan				
Tape measure with				
Plumb bob	3			
Range Pole				
A 1000 Foot Roll of	yellow Polyethylene Barricad	le Tape printed with the following message:		
	SAFFTY HAZARD KI	FEP AWAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24