HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 630A3710003

BRIDGE OWNER: MONTGOMERY COUNTY ROAD NAME: LOCK B SOUTH RD

CROSSING: BRANCH

COUNTY: MONTGOMERY

ROUTE: 0A371

SPECIAL CASE: 0

COUNTY SEQUENCE: 1

	TITUDE:: N 36.41795 DEGREES		LOG MILE: 5.33	
LON	GITUDE: W 87.30357 DEGREES		YEAR BUILT: 1984	
		TYPE OF SUPERSTRUCTURE -		
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM OF	R GIRDER APPR. SPAN: NOT APP	LICABLE	
		TYPE OF SUBSTRUCTURE		
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	IT ON CONCRETE SPREAD FOOTING FOUND	ATION	
BENTS:	NOT APPLICABLE			
PIERS:	NOT APPLICABLE			
		SCOUR EVALUATION		
		ur cannot be determined. The bridge sha		
during Signin	cant nood events. Monitor bridge	in lieu of installing scour countermeasur	es.	
		INSPECTION PROCEDURES ——————		
What Initiated the Call-out Inspection?		[] BridgeWatch Alert		
		[] TDOT District or Local Mainter		
		[] THP or Local Law Enforcemen		
		[] Other:		
[] - Span	neck on a bridge during floods movement - horizontally as we	ell as vertically		
	•	along curb line, both bridge rails and	d outer edge of bridge deck.	
	check for plumb of piers or ber	ts.		
	k for embankment erosion			
	k for drift build-up on piers or I			
		d compare to previous inspection		
[] - Revie	w the latest bridge inspection	report versus current field conditions		
If Closure is	recommended:			
Coun temp	ty or City Maintenance Person	ross road until bridge is secured and nel. Use Barricade Tape, traffic cones sts to stay off of the bridge until such	and/or traffic flares as	
[] - Conta] - Contact: (1) District Maintenance Supervisor (if bridge is State maintained)			
	(2) City or County Highway	Maintenance Official (if bridge is no	ot State maintained)	
	(3) Tennessee Highway Pa	trol and/or local law enforcement Offi	cers as appropriate	
	(4) TDOT Regional Bridge	Engineer		
	 The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team. 			

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	te District maintenance or local highway maintenance ridge on the selected detour route shall be checked		
[] - The bridge can be re-opened only after a TDO units and they are determined to be structura	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 648-5787		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 648-5740		
COUNTY SHERIFF'S OFFICE	(931) 648-0611		
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 			
COMMENTS:			
Suggested List of Equipment to conduct the Inspectatest Bridge Inspection Report Scour POA Report with the above Checklist	tion:		
Bridge Design Plans, if available			
Tape measure with weight Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade T	ane printed with the following message:		
SAFETY HAZADO KEE			

TDOT radio directory (State Personnel only)

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape