## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 630A4470001

BRIDGE OWNER: MONTGOMERY COUNTY
ROAD NAME: WATKINS FORD RD
CROSSING: BARTONS CREEK

LATITUDE:: N 36.34120 DEGREES LONGITUDE: W 87.30857 DEGREES

COUNTY: MONTGOMERY
ROUTE: 0A447
SPECIAL CASE: 0

COUNTY SEQUENCE: 1

LOG MILE: 0.07

YEAR BUILT: 1976

LON	IGHUDE: W 87.30857 DEGREES		YEAR BUILT: 1976
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	PRESTRESSED CONCRETE CONTI STRINGER/MULTI-BEAM OR GIRDE		NOT APPLICABLE
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	NT ON STEEL PILE FOUNDATION	
BENTS:	STEEL PILE BENT ON PILE FOUND	ATION	
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION	
	inknown foundations. Risk of scr icant flood events. Monitor bridg		bridge shall be monitored for distress termeasures.
		INSPECTION PROCEDURES =	
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert	
	·	[ ] TDOT District or Loca	al Maintenance Personnel
		[ ] THP or Local Law En	forcement Personnel
		[ ] Other:	
[ ] - Span 1. C 2. C [ ] - Chec [ ] - Chec	heck on a bridge during floods movement - horizontally as w Check displacement / deflectio Check for plumb of piers or be k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, and	ell as vertically n along curb line, both bridge nts. bents nd compare to previous inspe	
f Closure is	recommended:		
Coun temp	ity or City Maintenance Persor	nnel. Use Barricade Tape, trat rists to stay off of the bridge	cured and properly closed by District, ific cones and/or traffic flares as until such time as the bridge may
[ ] - Conta	act: (1) District Maintenance S	Supervisor ( if bridge is State	maintained )
	(2) City or County Highwa	y Maintenance Official ( if br	idge is not State maintained )
	(3) Tennessee Highway P	atrol and/or local law enforce	ment Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
	Bridge should remain closed u TDOT bridge inspection team.		daylight visual inspection is made

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	ith State District maintenance or local highway maintenance Any bridge on the selected detour route shall be checked		
[ ] - The bridge can be re-opened only after a units and they are determined to be stru	<ul> <li>The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.</li> </ul>		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 648-5787		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 648-5740		
COUNTY SHERIFF'S OFFICE	(931) 648-0611		
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct the li	nspection:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
_	cade Tape printed with the following message:		
SAFETY HAZARD			

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24