HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



ROAD CRO LATI	WNER: T NAME: E SSING: N ITUDE:: I	5023780013 OWN OF OAK MAIN ST IUD LICK CRE N 35.98560 N 84.55478		COUNTY: MORGAN ROUTE: 02378 SPECIAL CASE: 0 COUNTY SEQUENCE: 1 LOG MILE: 13.20 YEAR BUILT: 1940			
				TYPE OF SUPERSTRUCTURE			
MAIN SPAN:	CONCRET		JS - SLAB	APPR. SPAN: NOT APPLICABLE			
				TYPE OF SUBSTRUCTURE			
ABUTMENTS: I	MASONR	Y OR CONCRE	TE BLOCK A	BUTMENTS ON ROCK FOUNDATION			
BENTS:	NTS: NOT APPLICABLE						
PIERS:	RS: CONCRETE SOLID SHAFT PIER ON ROCK FOUNDATION						
				SCOUR EVALUATION			
	ration of	channel pro	tection or ri	nave been installed to reduce the risk of bridge failure during a flood prap should be reported to TDOT for assessment. Monitor bridge in lieu			
				INSPECTION PROCEDURES			
What Initiated	d the Ca	II-out Inspe	ction?	[] BridgeWatch Alert			
				[] TDOT District or Local Maintenance Personnel			
				[] THP or Local Law Enforcement Personnel			

- Things to check on a bridge during floods:
- [] Span movement horizontally as well as vertically
 - 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck.

[] Other:

- 2. Check for plumb of piers or bents.
- [] Check for embankment erosion
- [] Check for drift build-up on piers or bents
- [] Check pier exposure, if possible, and compare to previous inspection
- [] Review the latest bridge inspection report versus current field conditions

If Closure is recommended:

- [] Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.
- [] Contact: (1) District Maintenance Supervisor (if bridge is State maintained)
 - (2) City or County Highway Maintenance Official (if bridge is not State maintained)
 - (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate
 - (4) TDOT Regional Bridge Engineer
- [] The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.

PUBLICATION	DATE
-------------	------

07-Nov-24

BRIDGE ID 65023780013

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



- [] The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route.
- [] The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.

CONTACT PERSONNEL:

TELEPHONE NUMBER:

CITY MAYOR'S OFFICE

- (423) 539-3099
- [] Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.

COMMENTS: _	 	
-	 	
-	 	
-		

Suggested List of Equipment to conduct the Inspection:

Latest Bridge Inspection Report Scour POA Report with the above Checklist Bridge Design Plans, if available Tape measure with weight Plumb bob Range Pole A 1000 Foot Roll of yellow Polyethylene Barricade Tape printed with the following message: SAFETY HAZARD KEEP AWAY A Barricade Tape Dispenser with serrated cutter A roll of Duct Tape Traffic Cones - Minimum of four (4) Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers TDOT two-way radio (State Personnel only) and/or cellular telephone TDOT radio directory (State Personnel only)

PUBLICATION DATE 07-Nov-24

BRIDGE ID 65023780013